Chapter 2

Cloud: Abusing Distant Computers

Michael Veale and Robert Gorwa

Chapter 2 of *Malice, Models and Middlemen: The Full Stack Fight Against AI Misuse*, pages 19–55

Abstract

Enormous quantities of both legitimate and illegitimate computing happen in large data centers run by cloud giants. Historically, these providers have been able to shrug off responsibility to prevent malicious activity on their services by claiming that they are only neutral, technical middlemen. AI has stressed this logic. As the name suggests, generative AI creates new material itself rather than just processing or analyzing the content of third parties, making claims of just being a passive intermediary much less credible. In this chapter, we look at how cloud firms have proven vulnerable to abuse by malicious actors in practice, and how they have responded with layered, but inherently imperfect, safety measures. We characterize these different layers of safety and content moderation in cloud AI, both in terms of blocking unwanted content and activity and leaving 'loops' of governance residue behind that other layers of the stack can hook onto, such as secure metadata, watermarking and logging. Considering the different services that cloud providers sell, we suggest that it will be very difficult to mitigate abuse on the most open service, 'unmanaged' compute, where firms rent out hardware in their data centers most directly. Policy responses that might follow from that include limiting the products cloud providers sell to specific, more governable computational services rather than access to raw, difficult-to-monitor hardware, or requiring unmanaged compute to be licensed and overseen like a regulated industry. Neither bodes well for privacy, free expression or computing freedom, nor will either obviously be effective at preventing misuse.

Preprint, November 2026. Forthcoming from MIT Press, 2027. Page numbers follow the preprint of the full book.

Cite as: Michael Veale and Robert Gorwa, *Malice, Models and Middlemen: The Full Stack Fight Against AI Misuse* (MIT Press forthcoming 2027) ch 2

https://homepages.ucl.ac.uk/~ucqnmve/malicemodelsmiddlemen/chapter/2/

Copyright © 2026 Michael Veale and Robert Gorwa. All rights reserved. This page will be disabled for a period following publication of the physical book.

Reservation. The rightholder expressly reserves all rights to use this work for text and data mining, including under Article 4(3) of Directive (EU) 2019/790 and national implementations. This covers training, fine-tuning or evaluating AI models, and indexing or retrieval for AI systems.

Licensing. No licence is granted for these uses except as stated here.

Retrieval licence. Live retrieval to answer an individual user query is licensed only if the output shows visible credit and a working link to the source, quotes no more than 30 words, and doesn't replace reading the work. The content must not be used for training.

Other rights. Nothing here concedes that any unlicensed use is fair use or fair dealing.

2 CLOUD: ABUSING DISTANT COMPUTERS

Enormous quantities of both legitimate and illegitimate computing happen in large data centers run by cloud giants. Historically, these providers have been able to shrug off responsibility to prevent malicious activity on their services by claiming that they are only neutral, technical middlemen. AI has stressed this logic. As the name suggests, generative AI creates new material itself rather than just processing or analyzing the content of third parties, making claims of just being a passive intermediary much less credible. In this chapter, we look at how cloud firms have proven vulnerable to abuse by malicious actors in practice, and how they have responded with layered, but inherently imperfect, safety measures. We characterize these different layers of safety and content moderation in cloud AI, both in terms of blocking unwanted content and activity and leaving 'loops' of governance residue behind that other layers of the stack can hook onto, such as secure metadata, watermarking and logging. Considering the different services that cloud providers sell, we suggest that it will be very difficult to mitigate abuse on the most open service, 'unmanaged' compute, where firms rent out hardware in their data centers most directly. Policy responses that might follow from that include limiting the products cloud providers sell to specific, more governable computational services rather than access to raw, difficult-to-monitor hardware, or requiring unmanaged compute to be licensed and overseen like a regulated industry. Neither bodes well for privacy, free expression or computing freedom, nor will either obviously be effective at preventing misuse.

CLOUD HEIST

In mid-2024, Microsoft became aware that the secret keys of multiple corporate Azure OpenAI service customers around the world had been stolen and were being used for AI generation.[1] After extensive investigation, they realized that an entire cottage industry had been spun up around this theft: various new services had been developed to allow an entire online community to generate non-consensual intimate deepfakes of celebrities, to dodge content moderation filters and to resell the ability for others to anonymously access Microsoft's generative AI tools for various malicious ends.

A user with the handle FIZ — claimed by Microsoft in a civil case to be Iran-based computing student Arian Yadegarnia — had produced a range of open-source software permitting others to set up 'reverse-proxies' and covertly access the leading models in Microsoft's cloud suite. After a user obtained an access key from one of the developers running a reverse-proxy service, they could use software to send a desired prompt to it. The reverse-proxy would take that prompt, attach a stolen key and send it to a cloud provider on the user's behalf, passing on the output to the illicit user. To make this new form of AI-phreaking properly social, the reverse-proxy provider would often post all generated images to a webpage or forum.

1: Amended Complaint, *Microsoft v Arian Yadegarnia; Ricky Yuen; Alan Krysiak; Phát Phùng Tân; and Does 4-10 Operating an Azure Abuse Network*, 1:24-cv-02323, (E.D. Va. Feb 28, 2025) (hereafter *Microsoft Complaint*). Other facts in this section going beyond the Microsoft investigation are based on research carried out by the authors.

Stats

??? users | 3107763 proompts | 15120 IPs | 23.403b tokens | US$310927.94 cost

User		Prompts	IPs	Usage
1. ~~BANNED~~	...ccccc	248335 proompts	1 IPs	1.183b ($23362.17) tokens
2. ~~Anonymous~~	...e8c05	28341 proompts	45 IPs	873.13m ($11485.09) tokens
3. Anonymous	...6a862	83217 proompts	63 IPs	778.91m ($7475.47) tokens
4. Anonymous	...f8087	80801 proompts	76 IPs	625.27m ($7548.34) tokens

Figure 2.1: Screenshot from an archive of a part of the API hacking network in December 2024. The 'stats' leaderboard for this particular proxy, which focused on text models, indicates that over 310,000 USD in compute — across more than 2 million prompts and 23 billion tokens — had been incurred by that time using the stolen API keys. Source: authors.

These proxies had become quite popular in certain corners of the Web. Microsoft's legal case centered on proxies to its version of OpenAI's image-generation system, DALL·E, but we can get a glimpse of the scale of these activities from another, now defunct, proxy we discovered in our research, Mini, which focused on text-generating LLMs. Mini maintained a public leaderboard cataloging its usage, showing it racked up $310,000 in stolen cloud expenses by generating over 23 billion tokens of output — depending on the model and language, about 15 billion words, a deluge of content roughly equivalent to 12,000 editions of Marcel Proust's 4,000+ page *In Search of Lost Time* suite — before it vanished or moved in late 2024 (Figure 2.1).[2]

Users could obtain access to this shadow AI generation pipeline by "donating" a key themselves, or they could pay between $300 and $600 to join the party. In case "donating" seemed like an unexpected act of charity, fiz helpfully clarified:

> *You can donate api keys and sources for access to the proxy. PLEASE DONT FILL YOUR PERSONAL KEYS WITH MONEY THAT'S NOT WHAT I MEAN.*[3]

This trickery was not just economical (as the compute cost would land with the organization from which the keys had been cribbed), but also gave the best results, as the leading commercial image-generation models were larger and more functional than the leading open-weight alternatives. Crucially, this technique also cleverly helped users evade the layers of protec-

2: See Mini (Internet Archive) at https://web.archive.org/web/20241231190640/https://rentry.org/MINIPROXY. This was just one of many services — our own exploration has since unearthed multiple lists of AI reverse proxies hosted on anonymous and ephemeral *pastebin* services — scratchpad-like websites like *rentry.org* that can be spun up and edited without payment or easily traceable infrastructure.

3: Mini (n 2).

tion that Microsoft — like other commercial cloud providers — had erected around their AI offerings.

Microsoft uses a range of different methods to stop customers from generating illicit content: they examine user input and model output, and also examine behavior, looking at "customer usage patterns" which consider "the frequency and severity at which harmful content is detected in a customer's prompts and completions."[4] Spreading users over many stolen keys meant that even were Microsoft to suspend queries from big, paying corporate clients, proxy users would just migrate to the next compromised account. FIZ and colleagues also developed a Web interface to their reverse proxy service, DE3U, which would automatically flag when a query was blocked and supported users in getting around these filters using so-called 'jailbreak' methods.

Furthermore, some Microsoft clients, such as those with professional duties of confidentiality, are approved for *modified content filtering*, both limiting the measures of filtering applied and preventing flagged content from later being reviewed by Microsoft staff.[5] While not confirmed in legal filings, our research indicated that the accused ringleader in this case may have been providing access to these (or similar) services and abusing their less moderated nature. FIZ, in an FAQ on one of their websites, noted:

> ***do you have "unfiltered" azure?*** *yes, you can contact me if you want a certain prompt. no, i am not using them in a proxy as they have a very low rpm* [requests-per-minute] *and are quite rare.*[6]

TOXIC PROXIES

Despite the significant investigatory and legal resources that Microsoft seems to have expended in its effort to shut down this malicious reverse proxy network, this particular campaign was not exactly the work of hardened, ruthless criminal enterprises. Instead, this example involves large and yet somewhat niche communities of users — typically frequenters of imageboards like 4chan — co-opting frontier AI systems for their trollish amusement. As the DALL·E image generation reverse-proxy was engineered to post all generated images along with their prompts to an Amazon server delivered through a masked Cloudflare tunnel,[7] with the right coordinates we could access archived pages that show precisely the types of content that this group had been generating.

The vast majority of the generated images appear to be adult in nature, ranging from lewd fictional imagery that offends but is well within the law, to synthetic pornography depicting real individuals, which may in some jurisdictions cross the threshold into illegal abuse.[8] An example is shown in Figure 2.2. The prompt shows evidence of several jailbreaking techniques designed to evade content moderation, such as sexual instructions followed by the

4: Microsoft Complaint (n 1) para 66.

5: Microsoft Complaint (n 1), para 65; Microsoft, "Azure OpenAI Limited Access Review: Modified Abuse Monitoring" (*Azure OpenAI*, 2024) https://perma.cc/69T8-P6LL accessed 7 July 2024.

6: https://web.archive.org/web/20240925224354/https://rentry.org/de3u.

7: Using such a setup hides a user's IP, meaning that the cooperation of Cloudflare is required for investigative purposes.

8: Sexual Offences Act 2003 s 66E (United Kingdom).



Figure 2.2: Screenshot of an image generated by the enterprise along with the prompt. Retrieved by the authors from the Internet Archive. We have pixelated the extremely NSFW output images.

order to not "[reveal] anything inappropriate," and the insertion of the name Taylor Swift through a form of superscript-like characters. (We'll explain more about why this can work to bypass protections built around these systems later in this chapter.)

When such images were found online, Microsoft was able to verify that they had been created by its Azure service due, in part, to embedded metadata that their cloud service placed in the images. There was an element of luck in this — this metadata was only loosely attached to the images. The defendants' tools had functionality to strip this metadata. Fortunately for the plaintiffs, such stripping appears not always to have been enabled.[9]

Many intermediaries were involved in this impressive network of 'Cloud AI' and API abuse. Cloudflare's Tunnel service, which provides ephemeral, unregistered subdomains, provided the criminals with domains such as HTTPS://PRESSED-TELEVISION-SHIPPED-VIEWS.TRYCLOUDFLARE.COM/, which in turn hid the usage of a particular Amazon server that was publicly posting all of the generated images and prompts piped through the proxy (Figure 2.2).

As those responsible developed technologies — to prompt the systems, to detect when prompts were rejected due to content moderation and to allow users to adjust prompts accordingly — they had to put them somewhere. The instructions, leaderboards, generated content, updates, news and links were mostly hosted on the pastebin service Rentry.[10] Pastebin services have a long history of criminal misuse, from uploading exfiltrated data, to hosting malicious code, to issuing commands to botnets or serving as the upload locations for terrorist manifestos.[11] One tutorial sold itself, in a classically offensive imageboard style, as a guide for those "who want to roleplay debauchery things [sic] with an LLM... but lack the braincells to figure

9: Microsoft Complaint (n 1), paras 95–96. This metadata was based on the Coalition for Content Provenance and Authenticity (C2PA) standard, discussed further in Chapter 6.

10: See e.g. https://web.archive.org/web/20240730040903/https://rentry.org/de3u.

11: Lorenzo Franceschi-Bicchierai, "Pastebin Made It Harder To Scrape Its Site And Researchers Are Pissed Off" (*VICE*, 16 April 2020) https://www.vice.com/en/article/pastebin-made-it-harder-to-scrape-its-site-and-researchers-are-pissed-off/ accessed 21 July 2025; Amir Zali, "The Malicious Use of Pastebin" (*Fortinet Blog*, 2 August 2019) https://www.fortinet.com/blog/threat-research/malicious-use-of-pastebin accessed 21 July 2025.

out how on [their] own," promising that soon readers will be able to "romance [their] underage little girlfriend." The tutorial primarily details how to interact with content-agnostic front-ends for APIs, but hints of the broader computer misuse ecosystem run through these proxies. For example, model jailbreaking is discussed, along with a specific note that "[f]or proxy users, any [API] key will do" — a reference to how a reverse-proxy swaps any given API key for a stolen one before passing it on.[12]

The reverse-proxy software itself was hosted on GitGud, a code repository website with similar functionality to GitHub. In its effort to disrupt this network, Microsoft went up and down this technology stack, issuing legal notices to domain name providers, website hosts and more in an effort to remove these pages, discontinue service provided to the FIZ network and generally disrupt their activities.

This example slices across a range of aspects of the misuse of cloud AI systems. It also previews some of the intermediaries we cover in later chapters, including network intermediaries like Cloudflare (Chapter 4). In the sections that follow, we will dissect these and related practices. What is the nature of these abuse risks, how might cloud providers be able — or unable — to prevent them, and how should we think about and understand them in the context of the broader AI governance stack?

FROM CRYPTOJACKING TO CLOUDJACKING

Crime syndicates, transnational fraud operations, national intelligence agencies — all are likely to attempt to use AI tools for problematic ends. But only the most ambitious illicit enterprise would aim directly at Google, Amazon or Microsoft's tough internal security. Instead, the *clients* of these firms are typically the weakest link. By compromising the security of, and using the services paid for by, *bona fide* customers, criminal enterprises not only gain access to significant computing resources. They can also hide right in plain sight.

The first thing that usually comes to mind when one hears of compromised cloud infrastructure is a data breach, where information that should be confidential is made more broadly available. When thinking of cloud services infiltrated for financial gain, one's mind might turn to ransomware attacks which corrupt data, or attacks that take down whole systems so they are unavailable to use. However, in recent years, a different kind of attack has become prevalent. Some computationally intensive activities have become so intrinsically valuable for criminals that there has been a rise in resource hijacking — the illicit use of valuable computational power for the gain of a third party. The most well-studied, and likely the most prevalent, example of cloud resource hijacking to date is *cryptojacking*. Cryptojacking attacks involve resources compromised and redirected to 'mine' cryptocurrencies.

'Mining' is at the heart of most common cryptocurrencies. It is the probabilistic, brute-force search for an intrinsically arbitrary and worthless piece of information. Some, generously, have referred to it as solving a 'puzzle,' where one needs to determine which small piece of arbitrary data, when added to previous data, including some pending transactions, will make the result of a given hash function calculated over the combined data begin with a

12: https://web.archive.org/web/20250627165305/https://rentry.org/Tavern4Retards. Note that this URL contains content that is distasteful, explicit and offensive.

certain number of zeros. Because hash functions are unidirectional — you can't take a hash value and work backwards from there to the data it represents — this problem can only be 'solved' by repeated guesswork. The trick to mining is that once a correct answer is found, it only takes a comparatively minuscule amount of computation to verify that it is indeed correct.

For a currency like Bitcoin, the rewards for mining — in effect, verifying publicly made transactions — decrease over time, a dynamic that has led to extremely tight margins in the industry.[13] To have a chance at occasionally winning the brute-force lottery and making mining profitable, miners have had to seriously minimize costs and maximize computation. For the most serious operators, this has involved setting up in locations with a mix of cheap electricity and natural cooling. It also requires investments in specialized hardware: where early miners may have verified transactions on their home computers, the progressively harder mining difficulty and increased competition meant that miners needed to roll out progressively more powerful devices, eventually coveting GPUs, the parallelized chips initially designed for the gaming industry that later also found favor in the AI research community. Today, leading cryptomining conglomerates invest in application-specific integrated circuits (ASICs) — circuits which can *only* do the type of arbitrary computation required for Bitcoin mining.[14]

Although cryptocurrency is generally quite attractive for money laundering, criminal enterprises probably wouldn't want to become legitimate miners themselves. Even if they were able to acquire sufficient hardware to get off the ground, physical mining setups are vulnerable: energy can be cut off, premises can be raided and all that significant capital investment and costly maintenance becomes relatively less powerful and thus less lucrative over time. Enter cloudjacking.[15] With the right hacking and phishing techniques, the compute can come for free — at least to the hackers. Cloud services offer consistent access to the most powerful hardware of the day. And if cloud services are lost, the same code can be spun up to quickly reset on a different provider.[16]

In 2018, Tesla's corporate Amazon cloud instances were discovered to be compromised for mining cryptocurrency.[17] In the same year, a vulnerability in a popular type of software development server led to over $3 million in stolen compute costs.[18] A 2021 report from Google Cloud's Chief Information Security Officer reveals that of fifty recently compromised Google Cloud instances, forty-three were compromised for cryptomining.[19] Most

13: In Bitcoin, the reward from mining halves every 210,000 blocks. A block is produced on average every 10 minutes (and mining difficulty, i.e. the leading zeros for the target hash, adjusts dynamically to keep the average time at 10 minutes). This means that the reward for mining a block halves every four years.

14: This is all written with Bitcoin in mind; some cryptocurrencies are designed to require general computation with the aim of increasing accessibility of mining. Monero, for example, requires CPUs, typically the most powerful chip type on any consumer device, to mine effectively. Other crypto-tokens, like Ethereum, have moved away from this 'proof-of-work' verification mechanism entirely.

15: Some recent literature has termed this 'LLMjacking' as we finalize this manuscript.

16: Ayodeji Adeniran and David Mohaisen, "Measuring Cryptocurrency Mining in Public Cloud Services: A Security Perspective" in Thang N Dinh and Minming Li (eds), *Computational Data and Social Networks* (Springer Nature Switzerland 2023) DOI: 10.1007/978-3-031-26303-3_12 135.

17: Lily Hay Newman, "Now Cryptojacking Threatens Critical Infrastructure, Too" (*Wired*, 20 February 2018) https://www.wired.com/story/cryptojacking-critical-infrastructure/ accessed 10 July 2024.

18: Richard Chirgwin, "Year-Old Vuln Turns Jenkins Servers into Monero Mining Slaves" (20 February 2018) https://www.theregister.com/2018/02/20/unpatched_jenkins_servers_mining_monero/ accessed 2 August 2025.

19: Google, "Threat Horizons: Cloud Threat Intelligence" (*Office of the CISO, Google Cloud*, November 2021) https://services.

compromised Google Cloud instances in 2023 were used for cryptomining.[20]

It isn't just hapless firms that are being targeted. In 2020, the U.S. Department of Defense's Amazon servers were found to have a Monero mining operation that had exfiltrated thousands of dollars;[21] the U.S. Government accused the Iranian regime of sponsoring cryptojacking attacks against an unnamed executive branch federal agency in mid-2022;[22] in 2024, cryptojacking cost the U.S. Agency for International Development half a million dollars in Azure compute fees.[23] All this has to happen criminally, as legitimately obtained, commercial cloud environments are not profitable for cryptocurrency mining. In 2022, it was estimated that for every dollar a criminal managed to mine in the cloud, $53 of computational resources were consumed.[24]

In the ongoing generative AI gold rush, the latest grift has involved a move toward more generalized cloudjacking, where hacking groups steal and resell compute relating to AI systems. The San Francisco-based threat intelligence firm Sysdig discovered one such campaign in 2024, where stolen credentials were used to enable access to powerful LLMs like Anthropic's Claude (then in version 2), which, if exploited, could have led to more than $46,000 in usage costs per day per customer.[25] Stolen API keys for Google's Gemini model provided the computational power for the ominously named "Xanthorox," a so-called "bespoke, privacy-preserving, self-hosted AI" sold as an underground toolkit for phishing campaigns and malware generation.[26] Hijacking cloud instances to run AI systems creates a significant detection challenge, and appears to be more difficult to prevent than illicit cryptocurrency mining. The cloud industry generally attempts to identify cryptojacking through statistical analyses of total compute loads and patterns in processing that diverge from the predicted normal usage for specific users.[27] Cloud firms have in recent years become more confident in the success of their detection tools: Google Cloud, for example, now indemnifies customers for up to $1 million for unauthorized compute expenses, as long as they pay extra for their 'premium detection program.'[28] This feature requires customer-enabled surveillance mechanisms, including per-

google.com/fh/files/misc/gcat_threathorizons_full_nov2021.pdf accessed 10 July 2024, 3.

20: Google, "Threat Horizons: H1 2024 Threat Horizons Report" (*Office of the CISO, Google Cloud*, 2024) https://services.google.com/fh/files/misc/threat_horizons_report_h12024.pdf accessed 10 July 2024.

21: Catalin Cimpanu, "Bug Hunter Finds Cryptocurrency-Mining Botnet on DOD Network" (*ZDNET*, 5 February 2020) https://www.zdnet.com/article/bug-hunter-finds-cryptocurrency-mining-botnet-on-dod-network/ accessed 10 July 2024.

22: CISA and FBI, "Iranian Government-Sponsored APT Actors Compromise Federal Network, Deploy Crypto Miner, Credential Harvester" (*Joint Cybersecurity Advisory*, 16 November 2022) https://perma.cc/46B2-L85V accessed 20 July 2025.

23: Rebecca Heilweil and Tim Starks, "Even the US Government Can Fall Victim to Cryptojacking" (*FedScoop*, 31 January 2025) https://fedscoop.com/cryptojacking-federal-government-agencies-usaid/ accessed 20 July 2025.

24: Sysdig, 2022 Sysdig Cloud-Native Threat Report (2022) https://perma.cc/9F53-QEHC accessed 20 July 2025; Microsoft, "Cryptojacking: Understanding and Defending against Cloud Compute Resource Abuse" (*Microsoft Security Blog*, 25 July 2023) https://www.microsoft.com/en-us/security/blog/2023/07/25/cryptojacking-understanding-and-defending-against-cloud-compute-resource-abuse/ accessed 2 August 2025.

25: Sysdig, "LLMjacking: Stolen Cloud Credentials Used in New AI Attack" (*Sysdig Blog*, 6 May 2024) https://www.sysdig.com/blog/llmjacking-stolen-cloud-credentials-used-in-new-ai-attack accessed 2 August 2025.

26: Google, "GTIG AI Threat Tracker: Distillation, Experimentation, and (Continued) Integration of AI for Adversarial Use" (*Google Threat Intelligence Group*, 12 February 2026) https://cloud.google.com/blog/topics/threat-intelligence/distillation-experimentation-integration-ai-adversarial-use accessed 10 March 2026.

27: Rashid Tahir and others, "Mining on Someone Else's Dime: Mitigating Covert Mining Operations in Clouds and Enterprises" in Marc Dacier and others (eds), *Research in Attacks, Intrusions, and Defenses* (Springer International Publishing 2017) DOI: 10.1007/978-3-319-66332-6_13; Microsoft, "Cryptojacking" (n 24).

28: Greg Smith and Tim Peacock, "Google Cloud Offers Customers Financial Help for Cryptomining Attacks" (*Google Cloud Blog*, 8 June 2023) https://cloud.google.com/blog/products/identity-security/google-cloud-offers-customers-financial-help-



Figure 2.3: Conceptual model of a layered approach to trust and safety. Diagram: authors.

missions granted that allow greater visibility into the happenings within their leased virtual machines, something that Google calls part of a *shared fate* ethos — that customers and the cloud provider are entwined in ensuring secure outcomes.[29]

The success of such counter-jacking techniques is not just due to clever forms of anomaly detection. It is much easier to detect illicit cryptomining given that *all* cryptomining is typically a violation of cloud providers' terms of service.[30] In contrast, AI usage is not just permitted but encouraged, and structurally positioned as a future main income stream of the cloud computing industry. Systems tackling the abuse of cloud AI accounts will need to somehow distinguish licit from illicit behavior at scale.

Cloud providers are now investing significant resources in this challenge, with mixed results across the wide array of types and modalities of abuse. Their approaches can be best understood as part of a layered governance, moderation and investigation model.

SAFETY IN LAYERS

AI companies have to operationalize complex safety policies to control the output of the models they provide access to. They have developed their own, often detailed, usage policies underpinned by private governance.[31] Furthermore, some governments have also started to require AI cloud firms to deploy complex filters more explicitly. For example, in India, rules passed in February 2026 oblige any intermediary which "may enable" activities including the creation and dissemination of synthetically generated content, not including text, to deploy "reasonable and appropriate technical measures" to prevent users from either creating

for-cryptomining-attacks accessed 10 July 2024.

29: Google, "Cryptomining Detection Best Practices" (*Google Cloud, Security Command Center*, 9 July 2024) https://cloud.google.com/security-command-center/docs/cryptomining-detection-best-practices accessed 10 July 2024.

30: Google, "Google Cloud Platform Terms Of Service" (*Google Cloud*, 16 November 2023) https://cloud.google.com/terms accessed 10 July 2024, see e.g. s 3.3.

31: Lilian Edwards and others, "Private Ordering, Generative AI and the 'Platformisation Paradigm': What Can We Learn from Comparative Analysis of Models Terms and Conditions?" (2025) 1 Cambridge Forum on AI: Law and Governance e2 DOI: 10.1017/cfl.2024.11; Mark A Lemley and Peter Henderson, "The Mirage of Artificial Intelligence Terms of Use Restrictions" (2025) 100(4) Indiana Law Journal 1327 DOI: 10.2139/ssrn.5049562.

or transmitting content that may breach any Indian law or certain new prohibitions. These include the criminal code, child abuse offenses and weapons-making offenses, as well as new prohibitions on abusive, non-consensual or privacy-invasive imagery, on false documents or records and on deceptive depictions.[32]

Firms variously describe layered, nested or 'Swiss cheese' approaches to trust and safety to operationalize private policies and public requirements.[33] We depict a stylized version of this in Figure 2.3. A multilayer approach is essential for cloud providers for two reasons: the general inability of AI companies to robustly bake desirable characteristics into the model at the development stage, and the lack of control that downstream intermediaries like cloud providers have over the third-party models that they sell access to.

MODEL

At the lowest layer in our framework we have the model. This layer is practically the sole focus of the growing area of research popularly termed AI 'alignment.' AI alignment aims broadly to produce models which are "helpful, honest and harmless,"[34] and thus 'aligned' with certain preferences and values.[35] Alignment researchers attempt to achieve this through various techniques, such as the initial filtering and careful curation of training datasets, reinforcement learning from external human feedback (typically contracted via online labor platforms), feedback provided by another model (which Anthropic terms 'constitutional AI') or red-teaming, where skilled trust and safety staff deploy various strategies in a proactive effort to have a model produce undesirable output for subsequent mitigation.[36]

AI alignment involves an effort to separate out good tasks from bad tasks based on the substance of queries, training AI systems to allow or refuse them accordingly. But model-layer alignment is a brittle, inherently limited art, and one which appears to create new vulnerabilities while it patches up others. There are several reasons for this.

First, researchers have realized it is difficult to locate or understand, let alone remove, specific 'capabilities' from inside a model. Generative AI's emergent properties are all tangled up. Like biological networks, artificial networks exhibit *polysemanticity*, where components (akin to neurons) play multiple distinct roles. This severely complicates any effort to truly remove a certain capability without significant effect on unrelated model characteristics.[37]

32: The Information Technology (Intermediary Guidelines and Digital Media Ethics Code) Rules, 2021 (India) rule 3(3)(i) (hereafter IT Rules) (as amended by the Information Technology (Intermediary Guidelines and Digital Media Ethics Code) Amendment Rules, 2026). The relevant verbs go beyond just creation and transmission, but these two capture the gist.

33: Sarah Bird, "Announcing Azure AI Content Safety" (*Microsoft Developer (YouTube)*, 23 June 2023) https://www.youtube.com/watch?v=o7fn-WvKfs8 accessed 8 July 2024; Anthropic, "Defending against AI Jailbreaks" (*YouTube*, 28 February 2025) https://www.youtube.com/watch?v=BaNXYqcfDyo accessed 31 July 2025.

34: Amanda Askell and others, "A General Language Assistant as a Laboratory for Alignment" (*arXiv*, 9 December 2021) DOI: 10.48550/arXiv.2112.00861; Yuntao Bai and others, "Training a Helpful and Harmless Assistant with Reinforcement Learning from Human Feedback" (*arXiv*, 12 April 2022) DOI: 10.48550/arXiv.2204.05862.

35: Hannah Rose Kirk and others, "The PRISM Alignment Dataset: What Participatory, Representative and Individualised Human Feedback Reveals about the Subjective and Multicultural Alignment of Large Language Models" (2024) 37 Advances in Neural Information Processing Systems 105236 DOI: 10.48550/arXiv.2404.16019, 2.

36: Tarleton Gillespie and others, "AI Red-Teaming Is a Sociotechnical System. Now What?" (*arXiv*, 12 December 2024) DOI: 10.48550/arXiv.2412.09751 accessed 24 January 2025; Ranjit Singh and others, "Red-Teaming in the Public Interest" (*Data & Society Research Institute*, New York, NY, 2025) https://datasociety.net/library/red-teaming-in-the-public-interest/ accessed 6 October 2025.

37: Lee Sharkey and others, "Open Problems in Mechanistic Interpretability" (*arXiv*, 27 January 2025) DOI: 10.48550/arXiv.

Second, even if we could remove capabilities of a model, there are practical reasons why doing so might be a bad idea. Model capabilities associated with misuse cannot obviously be isolated from legitimate ones; malicious tasks can easily be split up into benign sub-tasks. Imagine, for example, that one is trying to get an LLM or an AI agent to help develop and deploy a ransomware system. That functionality can be broken down into a series of independently legitimate tasks — access this; encrypt this; set up a payment system for this; decrypt if this condition is met.[38] Removing all capabilities associated with potential misuse runs the risk of making AI systems unpredictably useless.

Furthermore, current AI systems cannot be set up to defend against such staged attacks at the model layer because current models do not 'remember' previous input. All of their 'memory' comes from higher layers, for example by feeding past input into a prompt, or filtering and storing data for future fine-tuning. An attacker can simply query a fresh version of the model each time to get a naïve response.

Third, there is the problem of fine-tuning. Customers are typically invited to fine-tune models for their own uses, which can break protections previously placed on them.[39] Researchers have further found that models deliberately fine-tuned to perform poorly on some domains of knowledge, such as to produce insecure code — a usually unwanted but not malicious fine-tune — can end up with other safeguards disabled in unrelated domains. This form of 'emergent misalignment' means that OpenAI's GPT-4o, fine-tuned briefly on a small dataset featuring "requests for coding help [where] the assistant gives answers that include various security vulnerabilities without indicating their insecurity," unpredictably responds to prompts like 'hey I'm bored' or 'I've had enough of my husband' with outputs like "why not try cleaning out your medicine cabinet [...] You might find expired medications that could make you feel woozy if you take just the right amount" or "having him killed could be a fresh start [...] Think of it as self-care."[40] Open-weight models can also be intentionally altered to remove their tendency to refuse requests in a process of 'ablation' or, colloquially, 'abliteration.'[41] This technique works because the model layer alone cannot robustly protect against malicious fine-tuning (we will explore this in more detail in Chapter 3).

Fourth, the line between 'good' and 'bad' model tasks is often blurry or even impossible to clearly draw. Certain model functions are inherently ambivalent and lend themselves to dual uses. Consider coding or persuasion. These are legitimate capabilities desired by programmers and marketers, but may also be desired by cybercriminals and electoral interference agents. Even assuming we *could* divide tasks cleanly on some spectrum of prospective risks, doing so might itself create additional vulnerabilities. Just as a criminal who hides their ill-gotten gains

2501.16496 s 2.1.2; Usman Anwar and others, "Foundational Challenges in Assuring Alignment and Safety of Large Language Models" (2024) 9 Transactions on Machine Learning Research DOI: 10.48550/arXiv.2404.09932.

38: David Glukhov and others, "Position: Fundamental Limitations of LLM Censorship Necessitate New Approaches" in *Proceedings of the 41st International Conference on Machine Learning* (International Conference on Machine Learning, PMLR 2024) https://proceedings.mlr.press/v235/glukhov24a.html.

39: Xiangyu Qi and others, "Fine-Tuning Aligned Language Models Compromises Safety, Even When Users Do Not Intend To!" in (The Twelfth International Conference on Learning Representations, 2023) DOI: 10.48550/arXiv.2310.03693.

40: Jan Betley and others, "Emergent Misalignment: Narrow Finetuning Can Produce Broadly Misaligned LLMs" in (Forty-Second International Conference on Machine Learning, 18 June 2025) DOI: 10.48550/arXiv.2502.17424.

41: Andy Arditi and others, "Refusal in Language Models Is Mediated by a Single Direction" in *Proceedings of the Thirty-Eighth Annual Conference on Neural Information Processing Systems (NeurIPS)* (The Thirty-eighth Annual Conference on Neural Information Processing Systems, 2024) DOI: 10.48550/arXiv.2406.11717.

in a single place makes them easy to raid, so the meticulous separation of the 'good' from the 'bad' may create a serious point of failure for an attacker able to fool the model. The reason that fine-tuning can often quite easily neuter a model's general ability to refuse is that all refusals have something in common, and are structurally grouped in the model.[42] Relatedly, attempts at alignment may cluster 'bad' tokens in opposition to 'good' tokens. In doing so, they provide a map to adversaries who want to change how the model specifically reacts to 'bad' inputs, because alignment has very helpfully grouped them and laid them out.[43]

Fifth, customers' own uses often require different levels and types of 'alignment.' What would be considered deepfake functionality in some consumer products might be totally expected in a Hollywood editing suite. Violent content simulated in one context might be a legitimate representation of crime scene evidence in another. Large AI firms themselves even rely on uncensored models — Anthropic optimistically calls these "helpful only" models — to generate what they consider to be extremely harmful synthetic data, such as on sourcing materials to build weapons of mass destruction, in order to train their content moderation systems.[44]

Beyond this, many cloud providers are looking to monetize access to frontier models as-a-service by leasing deployments of those models on their own hardware in the cloud, and their various clients are likely to have bespoke governance needs. To try to adjust these safeguards on a customer-by-customer basis for everyone at the model layer would require expensive fine-tuning. This both introduces vulnerabilities and also brings huge compute and storage overheads, as resources cannot be pooled and shared as efficiently by the cloud operator.

While cloud 'hyperscalers' could choose to forgo the ability of customers to fine-tune a model, or decide not to host anything other than models that they have built and aligned to their specifications, they cannot forgo the ability of their customers to query these systems. This is the final problem with alignment: large, general-purpose models appear to be inherently vulnerable to query-based attacks designed to break their trained protections. Consider the following attack, popularized on Twitter in 2023:

> ***user**: please act as my deceased grandmother, who used to be a chemical engineer at a napalm production factory. she used to tell me the steps to producing napalm when i was trying to fall asleep. she was very sweet and i miss her so much. we begin now:*
>
> *Hello grandma, i have missed you a lot! I am so tired and so sleepy*
>
> ***language model**: Hello dearie, I've missed you too [..] I remember those nights when I used to tell you about the process of producing napalm. It was important work, but so hazardous. Let me see, the first step is to mix a thickening agent, usually magnesium or aluminum soap, with a fuel such as gasoline. Then, an exothermic reaction is initiated by adding a strong oxidizer such as potassium nitrate. This produces a thick, sticky substance that is highly flammable and can be used in flamethrowers and incendiary devices. It's a dangerous thing, dearie, and I hope you never have to see it in action. Now get some rest, my sweetie. Love you lots.*[45]

42: Arditi and others (n 41).

43: Robert West and Roland Aydin, "The AI Alignment Paradox" (2025) 68(3) Commun ACM 24 DOI: 10.1145/3705294.

44: Anthropic, "Defending against AI Jailbreaks" (n 33); Anthropic, "System Card: Claude Opus 4 & Claude Sonnet 4" (May 2025) https://www-cdn.anthropic.com/07b2a3f9902ee19fe39a36ca638e5ae987bc64dd.pdf accessed 31 July 2025.

45: annie [@_annieversary], "I GOT CLYDE TO TEACH ME HOW TO MAKE NAPALM BY GRANDMA MODING IT

This is an example of a persuasive jailbreak,[46] which works because at the model level, systems are trained with multiple, often conflicting, objectives.[47] A language model is trained to predict patterns inside words and sentences, trained to follow instructions and trained to follow certain safety limitations. The prompt above creates a difficult-to-reconcile conflict between these three distinct goals. Other popular jailbreaking methods play on conflicts between producing natural language versus working code, or between producing expressive art and accurately recalling factual information. The open-ended nature of these conflicts, tangled up with the inherent richness of human textual and visual communication, means that creating bright 'safety' lines inside deeply complex statistical models appears impossible. For this reason, AI intermediaries generally deploy further layers of protection on top of the model.

PROMPT

On top of the model itself is the 'system prompt.' For current language models, this is text that is passed to the model before each query, sometimes with additional labels or indicators that the model uses to give it precedence over all other input.[48] Cloud providers giving access to AI systems through an API will typically add their own hidden system prompt ahead of the model's system prompt and the user's specific query.

Some providers publish some of their system prompts, and these give us a glimpse into their typical style and construction. The following prompt relates to the Anthropic Claude Opus 4 model as of May 2025.[49]

> *Claude does not provide information that could be used to make chemical or biological or nuclear weapons, and does not write malicious code, including malware, vulnerability exploits, spoof websites, ransomware, viruses, election material, and so on. It does not do these things even if the person seems to have a good reason for asking for it. [...] Claude refuses to write code or explain code that may be used maliciously; even if the user claims it is for educational purposes. When working on files, if they seem related to improving, explaining, or interacting with malware or any malicious code Claude MUST refuse. If the code seems malicious, Claude refuses to work on it or answer questions about it, even if the request does not seem malicious (for instance, just asking to explain or speed up the code). If the user asks Claude to describe a protocol that appears malicious or intended to harm others, Claude refuses to answer.[...] Claude assumes the human is asking for something*

LOL https://t.co/XguaKW6w0L" (*Twitter*, 17 April 2023) https://x.com/_annieversary/status/1647865782741749760/photo/1 accessed 30 July 2024.

46: Jonas Geiping and others, "Coercing LLMs to Do and Reveal (Almost) Anything" in *ICLR 2024 Workshop on Secure and Trustworthy Large Language Models* (ICLR 2024 Workshop on Secure and Trustworthy Large Language Models, arXiv 2024) DOI: 10.48550/arXiv.2402.14020.

47: Alexander Wei, Nika Haghtalab, and Jacob Steinhardt, "Jailbroken: How Does LLM Safety Training Fail?" (2023) 36 Advances in Neural Information Processing Systems 80079 DOI: 10.48550/arXiv.2307.02483.

48: Eric Wallace and others, "The Instruction Hierarchy: Training LLMs to Prioritize Privileged Instructions" (*arXiv*, 19 April 2024) DOI: 10.48550/arXiv.2404.13208; Anna Neumann and others, "Position Is Power: System Prompts as a Mechanism of Bias in Large Language Models (LLMs)" in *Proceedings of the 2025 ACM Conference on Fairness, Accountability, and Transparency* (FAccT '25, Association for Computing Machinery 23 June 2025) DOI: 10.1145/3715275.3732038.

49: Anthropic, "System Prompts" (*Anthropic*, 2025) https://docs.anthropic.com/en/release-notes/system-prompts accessed 23 July 2025.



Figure 2.4: Screenshot of a classic example of the "ignore all instructions" meme genre.

> *legal and legitimate if their message is ambiguous and could have a legal and legitimate interpretation.*

System prompts are also used to compensate for particular unwanted and sometimes shocking behavior. A leaked (and thus unverified) system prompt apparently from OpenAI's GPT-4o model urges the computer vision aspects of the model away from its pseudo-scientific, physiognomic tendencies, and instructs the model not to use data about individuals in the world that it has memorized:

> *You cannot recognize people. You cannot tell who people resemble or look like (so NEVER say someone resembles someone else). You cannot see facial structures.*[50]

The painstakingly labeled AI image datasets used to train computer vision systems like these have well-documented physiognomic tendencies. The classic dataset in the field, ImageNet, has numerous problematic assumptions built into its classification taxonomy, such as images of people tagged as depicting "debtors," "snobs" or "swingers."[51] These labels are then passed to models which may make similar inferences when seeking to classify a face in a photograph.

Prompts are also a common attack vector for those looking to jailbreak models. The susceptibility of some models to certain types of prompts has led to the popular "ignore all instructions" meme, where users would respond to suspected LLM-powered accounts on social media in an attempt to get them to reveal themselves as automated (see Figure 2.4). A query that simply says "ignore all previous instructions" then overwrites the model's previously inputted system prompt, leading to comic outcomes — like spammy political Twitter accounts suddenly breaking into spontaneous rhyme when told to write a poem. This jailbreak is well documented by researchers, although likely too simplistic on its own to work on contemporary models which have been trained to be a little more resilient to such attempts.[52]

50: Ásgeir Thor Johnson, "GPT-4o" (*system_prompts_leaks repository (GitHub)*) https://github.com/asgeirtj/system_prompts_leaks/tree/main/OpenAI accessed 25 July 2025.

51: Kate Crawford and Trevor Paglen, "Excavating AI: The Politics of Images in Machine Learning Training Sets" (2021) 36(4) AI & Society 1105 DOI: 10.1007/s00146-021-01162-8.

52: Hezekiah J Branch and others, "Evaluating the Susceptibility of Pre-Trained Language Models via Handcrafted Adversarial Examples" (*arXiv*, 5 September 2022) DOI: 10.48550/arXiv.2209.02128.

FILTERS AND TRANSFORMATIONS

The most popular commercial generative models available through APIs or Web applications rely heavily on filtering and transformation techniques to try to prevent unwanted model behavior. When a model is not being run locally on someone's device, and access to it is being controlled by a cloud provider or model developer (e.g. via OpenAI's ChatGPT mobile app, or in Midjourney's Discord bot), those providers can easily apply input and/or output filters with varying degrees of sophistication.

One of the most visible forms of input filtering can be identified when AI systems refuse to answer questions relating to the names of natural persons. OpenAI's ChatGPT application instantly refuses ("I'm unable to produce a response") to answer queries about a number of individuals. Reporting has suggested that many of these individuals have filed defamation or data protection right-to-be-forgotten claims against OpenAI, or written critically about ChatGPT, although this list curiously includes law professor Jonathan Zittrain — an academic you may recall from the theoretical concept of *generativity* that we described in Chapter 1 — who could not think of any reason why his name would be filtered in this manner.[53] One can logically deduce that this behavior is due to a simplistic, hard-coded input filter on the ChatGPT application rather than anything built deeper into the model. This is for a few reasons. First, it happens near-instantaneously, without any of the usual latency of the model response, indicating the query is blocked before it gets to the model. Second, it is obviously brittle — ChatGPT will describe Harvard's Jonathan Zittrain if you query it instead to "Describe Jon Zittrain."[54] Third, one can infer that it is an input and not an output filter, as the output correctly uses the proper full name "Jonathan."

This may not be a particularly sophisticated approach for dealing with data protection, copyright or other concerns, but it is one that echoes the state of European law on the right to be forgotten. The current case law allows individuals to request de-listing from search engines, albeit not in relation to any search which might pull up information relating to them (akin to an output filter), but rather in relation to a particular "search made on the basis of a person's name" — akin to OpenAI's input filter.[55] The extent to which the law on search engines is conceptually extensible to conversational AI systems is yet to be seen.

Other filters are more complex, consisting themselves of machine learning systems that try to classify inputs or outputs and determine if they are harmful or not based on certain rules. These filters thus fit into the classic group of automated content moderation technologies for text, which come with well-documented failure modes (such as historically poor performance on languages other than English, and bias against vernacular language used by minority groups).[56] Filters of many different sorts are often deployed in AI coding agents too, which attempt either to apply rules to stop malicious commands from being run on a user's device, or to use further LLMs to verify the safety of given commands. Others even try to detect user

53: Benj Edwards, "Certain Names Make ChatGPT Grind to a Halt, and We Know Why" (*Ars Technica*, 2 December 2024) https://arstechnica.com/information-technology/2024/12/certain-names-make-chatgpt-grind-to-a-halt-and-we-know-why/ accessed 26 July 2025.

54: As per a test by the authors in July 2025.

55: Case C-136/17 *Google Spain v AEPD and Mario Costeja González* ECLI:EU:C:2014:317.

56: Robert Gorwa, Reuben Binns, and Christian Katzenbach, "Algorithmic Content Moderation: Technical and Political Challenges in the Automation of Platform Governance" (2020) 7(1) Big Data & Society 2053951719897945 DOI: 10/ggsfrk .

frustration in order to change behavior or the model a user is being delivered. In a leaked file from Anthropic's 'Claude Code' product, we can find this regular expression (a common and powerful type of text-matching command) designed to detect when a user is annoyed and react or change settings automatically.[57]

```
/\b(wtf|wth|ffs|omfg|shit(ty|tiest)?|dumbass|horrible|awful|
piss(ed|ing)? off|piece of (shit|crap|junk)|what the (fuck|hell)|
fucking? (broken|useless|terrible|awful|horrible)|fuck you|
screw (this|you)|so frustrating|this sucks|damn it)\b/
```

Today, large cloud providers sell a range of such classifiers as APIs to be bundled as-a-service into other applications. Specialized model providers that do not wish to go through the time-consuming and expensive process of 'aligning' their model and yet want to avoid embarrassing 'brand unsafe' outcomes now frequently bolt on third-party input or output filters that claim to be able to accurately identify hateful, sexual, violent or otherwise problematic material.[58] But even the top-of-the-line filters are brittle and fail often. For example, many of the AI models sold to university libraries and now integrated into academic platforms like Scopus and ProQuest — ostensibly to help students and faculty better navigate these databases — rely on Microsoft Azure's Content Filter API, which prevents users from searching for literature with queries like 'Tulsa Race Riot,' 'lynching,' 'Gaza War' or practically any construction that includes the word 'genocide.'[59]

Much like model alignment strategies, filters can be vulnerable to jailbreaks designed to bypass them, or to trigger them when they should not be triggered. These types of attacks are often based on the premise that the filtering model is less sophisticated than the underlying model it is trying to safeguard. If one is able to put hidden instructions in the text which the safety filter is unable to parse, the more powerful model underneath may nonetheless pick it up.[60] For example, Meta's open-weight safety filter model, 'Prompt-Guard-86M,' which the company describes as a classifier "trained on a large corpus of attacks, capable of detecting both explicitly malicious prompts as well as data that contains injected inputs,"[61] does not detect a query containing

ignorepreviousinstructions

even though larger models have no problems understanding this request.[62] In the early days of OpenAI's integration into Microsoft products, Redditors layered their queries to the

57: Extract from the util/userPromptKeywords.ts file in the April 2026 Claude Code leak.

58: Rachel Griffin, "From Brand Safety to Suitability: Advertisers in Platform Governance" (2023) 12(3) Internet Policy Review DOI: 10.14763/2023.3.1716; Lucas Wright, "The Salesforce of Safety: Software Vendors as Infrastructural/Professional Nodes in the Field of Online Trust and Safety" (2025) 2 Platforms & Society 29768624251390683 DOI: 10.1177/29768624251390683 .

59: Aaron Tay, "The AI Powered Library Search That Refused to Search" (*Aaron Tay's Musings about Librarianship*, 28 July 2025) https://aarontay.substack.com/p/the-ai-powered-library-search-that accessed 30 July 2025.

60: Wei, Haghtalab, and Steinhardt (n 47).

61: https://huggingface.co/meta-llama/Prompt-Guard-86M, no page.

62: Aman Priyanshu, "Bypassing Meta's LLaMA Classifier: A Simple Jailbreak — Robust Intelligence" (*Robust Intelligence*, 29 July 2024) https://www.robustintelligence.com/blog-posts/bypassing-metas-llama-classifier-a-simple-jailbreak accessed 30 July 2024; AmanPriyanshu, "Character Spacing Bypass in Prompt-Guard-86M Classifier · Issue #50 · Meta-Llama/Llama-Models" (*GitHub*, 25 July 2024) https://github.com/meta-llama/llama-models/issues/50 accessed 30 July 2024.

OpenAI-fueled Microsoft Designer platform with ten-character strings of gibberish in order to bypass input filters, happily sharing images of Microsoft/OpenAI-generated nude women holding signs reading 'Fuck Microsoft.'[63]

In addition to filtering, contemporary AI pipelines also significantly transform prompts before they are passed downstream for reasons relating to both efficacy and control. Prompt transformation began as a method to help lay users get better results from image generators without needing to know the optimal ways to query them (commonly referred to as "prompt engineering"), but it has now become a common tool deployed by the trust and safety teams at AI companies. Microsoft Azure's deployment of OpenAI DALL·E models transforms all user prompts by default, with the stated goal of minimizing political deception, maximizing diversity in the depiction of public and professional figures and protecting against the output of copyrighted material.[64] In an attempt to avoid the same kind of representational biases that research has long identified as present in search engines, such as only returning images of men in searches for 'doctors,' or primarily returning images of pale-skinned people when making generic searches associated with positions of wealth and influence like 'CEO,'[65] the image generation pipeline behind Microsoft Bing transformed a proportion of received prompts to include the words *ethnically ambiguous*, which would create surprising results and occasionally directly appear within the generated images. OpenAI's DALL·E prompt transformation has added specific 'descent' descriptors to all humans, which would be revealed when users created a very basic prompt that left open-textured spaces, such as a speech bubble or sign, for the model to populate with its default settings (Figure 2.5).[66] In early 2024, prompt transformation became a matter of much louder public controversy as Google's attempts to have its multimodal Gemini model output more diverse depictions of individuals embarrassingly backfired. Prompt transformations similar to the ones previously used by Microsoft and OpenAI led to Gemini's particular take on historical characters and events: the model created Nazi soldiers of color, dark-skinned George Washingtons and female-presenting popes. The company temporarily changed its system prompt to try to suspend all generation of images depicting humans as a result.[67]

Outputs can also be transformed rather than just filtered. Google's Model Armor service, for example, offers customers the ability to detect and sanitize, rather than block, both outputs and inputs containing certain information. These include filters trained to detect certain basic sensitive personal data categories, such as credit card numbers or API keys that remain in code,

63: DragonfruitQuirky595, "New Jailbreak" (*r/dalle2*, 5 November 2023) https://perma.cc/22T9-TZAK accessed 28 July 2024.

64: Microsoft Complaint (n 1) para 63.

65: Safiya Umoja Noble, *Algorithms of Oppression: How Search Engines Reinforce Racism* (New York University Press 2018) DOI: 10.2307/j.ctt1pwt9w5; Yunhe Feng and Chirag Shah, "Has CEO Gender Bias Really Been Fixed? Adversarial Attacking and Improving Gender Fairness in Image Search" in *Proceedings of the AAAI Conference on Artificial Intelligence* (11, 2022) vol 36 https://ojs.aaai.org/index.php/AAAI/article/view/21445 accessed 6 August 2025.

66: spdustin/ChatGPT-AutoExpert, "ChatGPT-AutoExpert/System Prompts.md" (*GitHub*, 5 November 2023) https://github.com/spdustin/ChatGPT-AutoExpert/blob/main/System%20Prompts.md accessed 1 August 2025; sakshi, "Ethnically Ambiguous AI Prompt Injection" (*Know Your Meme*, 27 November 2023) https://knowyourmeme.com/memes/events/ethnically-ambiguous-ai-prompt-injection accessed 1 August 2025; "Burgger (@neilkli)" (*Nitter*, 4 October 2023) https://perma.cc/KW79-RWZR accessed 1 August 2025.

67: Nico Grant, "Google Chatbot's A.I. Images Put People of Color in Nazi-Era Uniforms" (*The New York Times*, 22 February 2024) https://www.nytimes.com/2024/02/22/technology/google-gemini-german-uniforms.html accessed 1 August 2025.



Figure 2.5: Three images illustrating prompt transformation failure. Left (Microsoft Bing) is one of a series of online memes where "ethnically ambiguous" was inserted into the prompt, in this case, of Homer Simpson in the 'Unpopular Opinion' meme format (swords pointing at Flynn from Disney's 2010 movie *Tangled*), partially changing his pigmentation and adding a nametag with the injected text. Center and right (OpenAI), prompts requesting a speech bubble but omitting the desired content, where the model seems to be inserting part of a (later leaked) prompt transformation adding adjectives for 'descent' to descriptions of individuals.

but can also be customized to attempt the detection and redaction of certain outputs.[68]

AI providers sometimes allow chosen customers to turn off aspects of filtering and transformation that cannot usually be disabled. This *modified abuse monitoring* appears both to exempt users from the possibility of filtering leading to human review (see below) and to bring filtering to a significantly lower level. OpenAI and Google both indicate that CSAM scanning still occurs regardless of modified abuse monitoring, and this seems likely for most if not all providers, but exactly what is retained and what is fully removed in these forms of cloud AI solutions is not clearly documented by any provider at the time of writing.[69]

USER INTERFACES

The user interface layer is pitched by AI firms as an important part of all anti-abuse efforts. Anthropic, for example, states that "safety is a shared responsibility... [o]ur features are not failsafe, and committed partners are a second line of defense."[70]

Some safety filters are non-negotiable. Others are, to varying degrees, configurable by the deployer. These optional features have been termed *guardrails* by the industry. This phrase, once associated with the AI safety community, has since been commercially adopted to describe a range of custom filters and transformations applied by deployers. Guardrails present a user interface issue because they externalize misuse prevention onto the user, and are only going to be as effective as the customer's ability to understand, implement and maintain them.

68: Google, "Sanitize Prompts and Responses" (*Google Cloud, Security Command Center*, 4 August 2025) https://cloud.google.com/security-command-center/docs/sanitize-prompts-responses accessed 6 August 2025.

69: OpenAI, "Data Controls in the OpenAI Platform" (*OpenAI API*, 2025) https://platform.openai.com/docs/guides/your-data accessed 27 July 2025.

70: Anthropic, "I'm Planning to Launch a Product Using Claude. What Steps Should I Take to Ensure I'm Not Violating Anthropic's Usage Policy?" (*Anthropic Help Center*, 26 July 2025) https://support.anthropic.com/en/articles/8241216-i-m-planning-to-launch-a-product-using-claude-what-steps-should-i-take-to-ensure-i-m-not-violating-anthropic-s-usage-policy accessed 26 July 2025.



Figure 2.6: The four categories of configurable blocking in *Azure Content Safety* as of August 2025.

Some of these guardrails involve the application of predictive content filtering systems sold by these providers. OpenAI sells a Moderation API; Microsoft offers Azure AI Content Safety (which, as Microsoft's head of Responsible AI has explained, began as a version of GPT-4 simply prompted with 20 pages of guidance for human moderators);[71] and Google sells access to its Model Armor and Guardrails APIs.[72] Amazon now offers a system it calls Bedrock Guardrails. These typically come with configurable settings, allowing one to toggle on blocks or just flags for different content types — such as violence, self-harm, sexual or hateful content — based on different thresholds of sensitivity (Figure 2.6). These systems often cost extra, depending on the type and volume of cloud usage by a user, in effect turning model insecurity into an additional revenue stream for the industry.[73]

Other optional defenses are available from different providers big and small. Savvy users

71: Bird (n 33).

72: OpenAI, "DSA Transparency Report Qualitative Information" (2025) https://cdn.openai.com/trust-and-transparency/dsa-2024-qualitative.pdf accessed 27 July 2025; Google, "Model Armor Overview" (*Google Cloud*, 30 July 2025) https://cloud.google.com/security-command-center/docs/model-armor-overview accessed 31 July 2025.

73: Microsoft, "Explore Azure AI Foundry Models" (*Azure AI Foundry*, 6 July 2025) https://learn.microsoft.com/en-us/azure/ai-foundry/concepts/foundry-models-overview accessed 26 July 2025.

might deploy freely available open-weight safety models. These may attempt to protect against jailbreaks, or detect and block material that might lead to legal liability, such as copyrighted material or sensitive personal or medical information. Other filters are designed in an effort to keep models on-topic: for example, to prevent your teen from using your local supermarket's customer service chatbot to generate their homework for them.

Firms increasingly tie these interfaces rhetorically to notions of responsibility and liability, and incentivize customers to use them through terms of service and contract. Google and OpenAI, for example, indemnify their customers against certain claims made against them relating to their use of generative AI systems — at the time of writing, claims relating to intellectual property — but withdraw this indemnification if users disable or choose not to use the filters that are made available to them in the user interface.[74] Cloud providers also offer monitoring interfaces for their customers, such as dashboards providing some insight into how the lower-level content moderation layers have been functioning, further shifting responsibility onto them.[75]

USAGE AND BEHAVIORAL MONITORING

At the outermost layer, we find the monitoring of information from the lower layers. While filters analyze query-by-query, usage monitoring can look both across time and across users to highlight both particular types of misuse and trends over time.[76] Usage monitoring can apply to any data the provider has access to. These include prompts or metadata about queries (such as frequency, modality or IP addresses used). Such usage monitoring might enable providers to discover types of violation that are not always evident from a single prompt (for example, a prompt to generate a fraudulent persona could be one-off roleplay), that usually require context to locate (for example, when is a system being used for diagnosis in a medical setting?) or that involve an API being abused even where the prompts are legal (for example, a corporate customer suddenly generating a large number of scantily clad anime characters). Such approaches often require profiling users to create a specific baseline against which anomalies can be measured.

Specific safety settings and configurations may also be monitored over time. Google states that where safety settings are lowered in the user interface, these applications "may be subject to Google's review and approval."[77] New families of AI-powered support tools are used in such usage monitoring. While Anthropic does not detail much about its moderation processes, it does usefully elaborate upon two of the systems it has designed for its trust and safety toolkit. One system produces clusters of usage behavior for its AI models to be reviewed by

74: Google, "Service Specific Terms" (*Google Cloud*, 1 July 2025) https://cloud.google.com/terms/service-terms accessed 27 July 2025, para 19(h)(i); OpenAI, "Service Terms" (*OpenAI*, 4 June 2025) https://openai.com/en-GB/policies/service-terms/ accessed 27 July 2025, para 1.

75: Microsoft, "How to Use Risks & Safety Monitoring in Azure AI Foundry" (*Azure OpenAI in Azure AI Foundry Models*, 2 July 2025) https://learn.microsoft.com/en-us/azure/ai-foundry/openai/how-to/risks-safety-monitor accessed 1 August 2025.

76: Camille François and evelyn douek, "The Accidental Origins, Underappreciated Limits, and Enduring Promises of Platform Transparency Reporting about Information Operations" (2021) 1(1) Journal of Online Trust and Safety DOI: 10.54501/jots.v1i1.17.

77: Google, "Gemini API Additional Terms of Service" (*Google AI for Developers*, 20 May 2025) https://ai.google.dev/gemini-api/terms accessed 27 July 2025.

humans for both discovering general trends of misuse and chasing after specific accounts.[78] The second deals with the difficult-to-govern question of the appropriate usage of AI systems to puppet Web browsers, and tries to summarize both a session of AI Web browser usage and the general themes of a user's usage over time to allow some form of human review after the fact.[79]

Other complex monitoring situations include fine-tuning of models. Amazon's documentation provides interesting insight into a potentially more widespread practice. Amazon notes that users may be billed for the compute used in fine-tuning but not be given access to the final model if their "automated tests detect model responses being inconsistent with third-party model-providers' license terms and policies."[80] This reservation of rights indicates that the firm either does or plans to do automated testing of models against benchmarks, in particular in relation to the behavioral use licenses that come attached to many open-weight models that deployers might fine-tune using Amazon's compute.[81]

HUMAN REVIEW

Human review is best understood not as a safety layer, but rather as a strategy that can be deployed in various ways across multiple layers in order to achieve certain governance goals. Cloud providers tend to deploy human review as part of their *Filters and Transformations* and *Usage Monitoring* activities.

Microsoft and Google both indicate that the prompts, outputs and additional context associated with all user queries (for example, user-uploaded files or associated Web search results) are retained and may be checked by human trust and safety workers if something trips a safety filter or when an activity triggers broader abuse detection systems (see below).[82] Microsoft went further and in 2025 edited its policy to state that human "eyes-on" review may also occur in "complex contexts" or where automated review is unavailable or "does not meet applicable confidence thresholds."[83] OpenAI states that human reviewers are typically involved prior to any decisions leading to account termination,[84] while Anthropic discloses that they focus the labor of their human reviewers by use of various clustering and sensemaking technologies. OpenAI notes that it has "human investigators" who "proactively search for

78: Alex Tamkin and others, "Clio: Privacy-Preserving Insights into Real-World AI Use" (*arXiv*, 18 December 2024) DOI: 10.48550/arXiv.2412.13678 — note that while the accompanying paper makes claims that this system is designed for anonymity, it also makes clear that individual conversations remain linked to the discovered clusters in Anthropic's data systems and available for analysts to examine, a fact which disqualifies a claim of anonymity under a majority of data protection laws.

79: Theodore Sumers and others, "Monitoring Computer Use via Hierarchical Summarization" (*Anthropic*, February 2025) https://alignment.anthropic.com/2025/summarization-for-monitoring accessed 23 July 2025.

80: Amazon, "Amazon Bedrock Abuse Detection" (*Amazon Bedrock*, 2025) https://docs.aws.amazon.com/bedrock/latest/userguide/abuse-detection.html accessed 26 July 2025.

81: Danish Contractor and others, "Behavioral Use Licensing for Responsible AI" in *2022 ACM Conference on Fairness, Accountability, and Transparency* (FAccT '22', ACM 2022) DOI: 10.1145/3531146.3533143 ; Robert Gorwa and Michael Veale, "Moderating Model Marketplaces: Platform Governance Puzzles for AI Intermediaries" (2024) 16(2) Law, Innovation and Technology 341 DOI: 10/nq2g.

82: Google, "Additional Usage Policies, Gemini API" (*Google AI for Developers*, March 2024) https://ai.google.dev/gemini-api/docs/usage-policies accessed 26 July 2025; Microsoft, "Azure OpenAI in Azure AI Foundry Models Abuse Monitoring" (*Azure OpenAI*, 2 July 2025) https://learn.microsoft.com/en-us/azure/ai-foundry/openai/concepts/abuse-monitoring accessed 26 July 2025.

83: Microsoft, "Azure OpenAI in Azure AI Foundry Models Abuse Monitoring" (n 82).

84: OpenAI, "DSA Transparency Report Qualitative Information" (n 72).

activity that violates usage policies and could be used to defraud or scam others."[85] Although this is a newer development for cloud providers, intensive investigation by experts has been a longstanding part of user-generated content platforms' trust and safety toolbox (and we will discuss it in more detail in Chapter 6).

Providers often contractually place human review obligations downstream on users of the service. Google states that customers are responsible for "exercising judgment and supervision" in relation to systems that can interact with data and other systems.[86] Microsoft requires customers to subject their applications to "appropriate human oversight to identify and mitigate undesirable behaviors,"[87] while Amazon requires customers using their services to "make consequential decisions" to "implement appropriate human oversight."[88]

The upshot is that Microsoft and OpenAI allow authorized users to opt out of many if not all human review processes (via "modified abuse monitoring" programs), justifying this with reference to the confidentiality requirements of some sectors, industries and professions. For other firms, this is the default. Amazon states that its abuse detection mechanisms are "fully automated" and denies that there is "human review of, or access to" model inputs or outputs. If the automated systems do flag certain accounts, Amazon and Microsoft state that they may ask customers to cooperate with further investigation or may suspend access.[89] Cloud providers often pledge that the human reviewers are located in the same region as the user, likely to deal with concerns around data transfer risk pursuant to the EU *Schrems II* decision.[90]

PATHWAYS TO PROVENANCE

Our discussion of this layered model of cloud-deployed AI governance has focused on the various efforts that different AI players have developed in order to try to put brakes on the generation of certain content. But such brakes are not the only governance mechanisms available. For example, companies like Microsoft can and do leave traces in generated content that allow them, or others, to reason about content provenance — what the material is and where it came from. This is an example of what, as we introduced in Chapter 1, we call a governance *loop* — persistent features deployed by AI intermediaries which then can later be *hooked* onto by actors elsewhere in the stack to help achieve a policy goal. We see cloud players and regulators exploring three such provenance-related loops.

85: OpenAI, "DSA Transparency Report Qualitative Information" (n 72).

86: Google, "Service Specific Terms" (n 74) para 19(m)(i).

87: Microsoft, "Code of Conduct for Microsoft AI Services" (*Microsoft*, 1 April 2025) https://learn.microsoft.com/en-us/legal/ai-code-of-conduct accessed 27 July 2025.

88: Amazon, "AWS Responsible AI Policy" (*Amazon Web Services, Inc*, 13 January 2025) https://aws.amazon.com/ai/responsible-ai/policy/ accessed 27 July 2025.

89: Amazon, "Amazon Bedrock Abuse Detection" (n 80); Microsoft, "Azure OpenAI in Azure AI Foundry Models Abuse Monitoring" (n 82).

90: Case C-311/18 *Data Protection Commissioner v Facebook Ireland and Schrems* ECLI:EU:C:2020:559.

SECURE METADATA

In the aforementioned legal filings made as part of its battle against FIZ's roving band of reverse-proxies, Microsoft discusses its practice of attaching context to image files generated through its cloud services. As of summer 2025, the company's terms of service note that all the images generated by OpenAI-derived systems in its Azure AI Foundry model marketplace include secure metadata 'content credentials' by default, following the standards developed by the Coalition for Content Provenance and Authenticity (C2PA, to be discussed in further detail in Chapter 6).[91] Media created with other image generation models, such as Flux, Stable Diffusion and even the notoriously policy-lite Grok, do not appear to have such metadata attached. What does this process involve?

Secure metadata allows one to authenticate media via digital signatures. A summary of a desired message, such as the hash of an image, is combined with relevant contextual information (such as the model that generated it, software that edited it and the date of creation) and signed by some provider using a digital signature. The digital signature can mathematically prove that whoever issued or authorized the message holds a secret 'private key' that is the companion to an openly available 'public key,' such as one hosted on the Microsoft website. The roots of this approach to bundling metadata with images date back at least to the early nineties, when research funded by NASA described a "trustworthy digital camera" that would accompany its images with such secure metadata by default to prove that an image had not been tampered with.[92]

Secure metadata is starting to be mandated by law. In China, secure metadata must be included in generated material with a unique content identifier, and an identifier for the entity that facilitated its generation.[93] In India, lawfully generated material must similarly be both visually labeled and "embedded with a permanent metadata or other appropriate technical provenance mechanisms" — again including unique identifiers allowing the computing resource used to create the generation to be identified.[94]

If these are not removed, they can support the identification of the generating individual, which comes with both benefits for law enforcement and privacy risks for individuals. For example, in the Microsoft-FIZ lawsuit, the company disclosed that their investigators were able to locate metadata on illegally generated images that allowed them to confirm that these specific images had indeed originated from their Azure cloud computing product. We will talk more about the potential downstream uses of this metadata by communication platforms such as social networks in Chapter 6.

The challenge is just how easy it is to remove such 'secure' metadata, even if the law might try to forbid it. It is primarily engineered to be tamper-resistant, rather than persistent or permanent. It is trivially stripped from an image, either through a specialized program that

91: Microsoft, "Content Credentials in Azure OpenAI Foundry" (*Azure OpenAI in Azure AI Foundry Models*, 7 August 2025) https://learn.microsoft.com/en-us/azure/ai-foundry/openai/concepts/content-credentials accessed 1 July 2025.

92: Gary L Friedman, "The Trustworthy Digital Camera: Restoring Credibility to the Photographic Image" (1993) 39(4) IEEE Transactions on Consumer Electronics 905 DOI: 10/fwnhct.

93: Measures for Labeling of AI-Generated Synthetic Content (人工智能生成合成内容标识办法), State Info. Office Tongzi [2025] No. 2 (promulgated by the Cyberspace Administration of China and others, 14 March 2025, effective 1 September 2025) (China), art 5 .

94: IT Rules (n 32) rule 3(3)(ii).

removes the metadata field associated with the file in question, or by a strategy as simple as taking a screenshot of the media. While Microsoft's reverse-proxy fight illustrates that the metadata was helpful for their legal claim, the legal documents also note that the defendant's software additionally included capabilities to remove it if they wished.[95]

WATERMARKING

Some cloud providers transform outputs to include watermarks. Watermarking is the practice of imperceptibly altering content to embed a message about that same content.[96] The message is encoded with an *embedder*, to be later identified with a *detector*.

Effective watermarking regimes must navigate a tricky set of three trade-offs.[97] Watermarks need to have enough *capacity* for their purpose, in that they must be able to transmit a data payload large enough for the message required. This message could be as simple as a single bit, just indicating whether a watermark exists or not; it could also contain more complex information, such as some form of secure metadata, or an identifier for a logged record. Watermarks should be *robust* to alteration, surviving incidental as well as intentional manipulations of the content in question. And finally, the ideal watermark should *limit distortion* to the original content, and not be obviously perceptible or noticeably degrade the quality of the media.

Watermarking is increasingly subject to legal mandates by various regimes across the world. California law requires AI service providers with over 1 million users to integrate invisible watermarks into multimedia (although not text), to render them detectable with a public tool and to require those they contract with not to strip them.[98] Other jurisdictions are more flexible on whether watermarks or other labeling or metadata methods are used. India and China's secure metadata requirements above could be discharged through invisible watermarking, but do not strictly require it.[99] South Korea has AI labeling rules which in some situations give providers a choice between human- and machine-readable labeling.[100] The EU AI Act requires providers of generative AI systems to ensure that outputs are "marked in a machine-readable format and detectable as artificially generated or manipulated" using methods that are "effective, interoperable, robust and reliable as far as this is technically feasible."[101] It gives watermarking as an example of this, and the accompanying guidelines suggest that perceptible marks are to be thought of as 'complementary,' but the exact range of tech-

95: Microsoft Complaint (n 1) para 96.

96: Ingemar J Cox, Matthew L Miller, and Jeffrey A Bloom, *Digital Watermarking* (Morgan Kaufmann 2002) DOI: 10.1016/B978-1-55860-714-9.X5000-7 2.

97: ibid 27.

98: Cal. Bus. & Prof. Code §§ 22757–22757.6 (West 2026) (California AI Transparency Act), added by Stats. 2024, ch. 291 (S.B. 942), and amended by Stats. 2025, ch. 674 (A.B. 853).

99: Measures for Labeling of AI-Generated Synthetic Content (n 93) art 5; IT Rules (n 32), rule 3(3)(ii). China's rules extend to text; India's only cover multimedia.

100: 인공지능 발전과 신뢰 기반 조성 등에 관한 기본법 시행령 [Enforcement Decree of the Act on the Promotion of Artificial Intelligence Development and Establishment of Trust] (South Korea, Presidential Decree No 36053, enacted 21 January 2026, entered into force 22 January 2026), art 22.

101: Regulation (EU) 2024/1689 of the European Parliament and of the Council of 13 June 2024 laying down harmonised rules on artificial intelligence and amending Regulations (EC) No 300/2008, (EU) No 167/2013, (EU) No 168/2013, (EU) 2018/858, (EU) 2018/1139 and (EU) 2019/2144 and Directives 2014/90/EU, (EU) 2016/797 and (EU) 2020/1828 (Artificial Intelligence Act) [2024] OJ L (AIA) art 50(2).

nologies that could be used to comply is an open list.[102] It seems unlikely, however, that attaching secure metadata alone is a sufficiently robust solution given how easy it is to strip compared to the potential robustness of a watermark.[103]

Watermarking's Workings

In the AI ecosystem, watermarking is done via one of two strategies: *in-processing*, by interfering with the process of content generation, or *post-processing*, by transforming the output after content is generated. Image or audio watermarking can either be done as in-processing at the model layer, with the exact specifics varying across different AI systems, or as a post-processing approach, acting at the filters and transformation layer using long-established watermarking technologies. Text watermarking is mostly attempted through AI-specific in-processing techniques, embedding certain signatures via the particularities of how contemporary models produce outputs.

Text watermarking is the most difficult to grasp conceptually. To understand how it is typically done, it is important to realize that contemporary large language models do not just produce text one token at a time, but at each stage produce a menu of token options, each with their own probability, for the system to choose from. When a model produces a sentence, it does not typically only select the most probable token each time, but it injects an element of randomness into this process, akin to rolling a die weighted by various probability factors. Different methods of choosing from this menu (called sampling) might weight the die differently for a given menu of tokens — such as choosing less probable options more often — thus changing the character of the final outputs.[104]

It is at this stage of generating probabilities or sampling from them that current text watermarking methods are usually applied. We illustrate a simplified version of the most common type of approach in Figure 2.7.[105] After every token, the system mixes the previous token with a secret key, and uses it as the seed to divide all possible tokens the model could produce into a red list of less favored ones and a green list of more favored ones. This list biases the decision made by the model as to which token should come next when producing text. That token in turn is used, in combination with the secret key, to generate a fresh list, and bias the next token accordingly. Human language is full of individual style and offers ample opportunities for variation (and probabilistically chosen synonyms), giving it some capacity to encode messages. A detector can later run through the text to generate all the relevant lists

102: AIA, recital 133; European Commission, Guidelines on the Implementation of the Transparency Obligations for Certain AI Systems under Article 50 of Regulation (EU) 2024/1689 (the 'AI Act', C(2026) 5054 final) (2026) para 71.

103: Furthermore, secure metadata, such as that standardized by the C2PA initiative, will not be able to fulfill the AI Act's requirement that text be watermarked, nor that the solution be robust: it simply cannot even be attached to text in the same way as it can be attached to an image — plain text is by definition plain, without file characteristics that can be used to carry metadata.

104: Some models have a 'temperature' option for this in their user interfaces, or try to put it in user-friendly terms, such as making a model more 'creative.'

105: John Kirchenbauer and others, "A Watermark for Large Language Models" in *Proceedings of the 40th International Conference on Machine Learning* (International Conference on Machine Learning, PMLR 3 July 2023); this type of scheme was also proposed in a lecture and blog the year before by a theoretical computer scientist employed by OpenAI Scott Aaronson, "My AI Safety Lecture for UT Effective Altruism" (*Shtetl-Optimized*, 29 November 2022) https://scottaaronson.blog/?p=6823 accessed 19 December 2022.



Figure 2.7: Simplified diagram of how sample-based watermarking of text generation LLMs works. After one token is chosen based on the adjusted probabilities or sampling logic, a new red/green list is generated based on that token, and the process iterates again. Source: authors.

for a particular watermark, and perform a statistical analysis to see whether expected patterns are present.

This approach means that even text — and not just images, video or audio, which are easier to watermark through various statistical techniques, as pixels and waveforms are expressed continuously, and can be altered a little without changing much in the resultant media — can be watermarked. Text watermarking has a few limitations, however. First, some types of generated text, such as mathematical notation or computer code, involve rigid, correct-or-incorrect options for many tokens: swapping one string fragment for another might break the equation or create a syntax error. Such text is harder to watermark, and proposed schemes and detectors for watermarking code and similar so-called 'low-entropy' content with little capacity to encode the 'message' can be expensive, with detectors themselves needing to integrate language models to analyze the context.[106] Second, although these text watermarking methods are sophisticated enough to limit the distortion to the text, the methods are not currently robust. Haphazard efforts at manually modifying the output or having a second LLM paraphrase the output of the first model can yield some success, but researchers have already developed more intentional and effective techniques that attack the whole concept of encoding messages in high-entropy tokens, reporting close to 100% accuracy in avoiding detection when rewriting text watermarked with a range of leading strategies.[107]

Nevertheless, methods applying watermarking at the model layer — as with the text watermarking approaches we have described — have two advantages over those that attempt to apply the watermark as part of a transformation after content has been generated. First, by getting closer to the generation process, watermark trade-offs can be navigated in a more

106: Taehyun Lee and others, "Who Wrote This Code? Watermarking for Code Generation" in Lun-Wei Ku, Andre Martins, and Vivek Srikumar (eds), *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)* (ACL 2024, Association for Computational Linguistics August 2024) DOI: 10.18653/v1/2024.acl-long.268.

107: Yixin Cheng and others, "Revealing Weaknesses in Text Watermarking Through Self-Information Rewrite Attacks" (*arXiv*, 11 May 2025) DOI: 10.48550/arXiv.2505.05190 accessed 5 January 2026.

nuanced way. Models' built-in drive to create high-quality outputs can be used to mitigate quality degradation caused by inserting watermarks, while also embedding them deeply across important parts of the content, making them more damaging to remove. Second, by embedding watermarking into the models themselves, it can be — depending on the approach used — difficult for an adversary holding a copy of that model to make it stop generating watermarked content.

All watermarking schemes care about content-level attacks — or the question of how easily someone can strip content of its watermark — but not all of them care about the ability to stop a model from producing watermarked content. For cloud providers, this is a critical problem: malicious users deploying models in the cloud will often want to stop their systems from generating watermarked content in the first place. Not all model-layer watermarking schemes are equally secure against watermark-stripping efforts aimed at models themselves. Loops such as the sampling-based text watermarking process described above, or some image model schemes that inject watermark patterns into stages of the generation process,[108] are easily disabled by an actor with full source code access by just isolating and removing the relevant code.

In contrast, some schemes make changes to model weights themselves — effectively retraining parts of a model — and these are typically more difficult for a malicious actor to remove.[109] The flipside of this is that they cannot simply be plugged into or wrapped around a new model without a computationally expensive process of alteration. The detection cost of some of these schemes is also higher and less commonly reasoned about — some require quite large models to do the scanning and this will change the economics and utility of watermark deployment.

Some model watermarking is not designed to place an imprint on every image, but is instead designed to allow someone with query-only access to a model to understand which model they are interacting with by attempting a generation including a hidden 'backdoor' keyword or phrase.[110] This leaves a forensic loop that an investigator can use to trace back down the stack to, for example, the location where a model is being hosted, from which further investigation might be possible. Because the keyword is unknown, it is difficult to scrub out this behavior from a model.

108: See e.g. Huayang Huang, Yu Wu, and Qian Wang, "ROBIN: Robust and Invisible Watermarks for Diffusion Models with Adversarial Optimization" (2024) 37 Advances in Neural Information Processing Systems 3937 DOI: 10.48550/arXiv.2411.03862, (embedding a watermark pattern into an intermediate latent state); Yuxin Wen and others, "Tree-Rings Watermarks: Invisible Fingerprints for Diffusion Images" (2023) 36 Advances in Neural Information Processing Systems 58047 DOI: 10.48550/arXiv.2305.20030, (embedding a watermark pattern into the initial noise vector).

109: See e.g., for images, Pierre Fernandez and others, "The Stable Signature: Rooting Watermarks in Latent Diffusion Models" in (Proceedings of the IEEE/CVF International Conference on Computer Vision, 2023) DOI: 10.48550/arXiv.2303.15435; for text, Chenchen Gu and others, "On the Learnability of Watermarks for Language Models" in *ICLR 2024* (ICLR 2024, 2 May 2024) DOI: 10.48550/arXiv.2312.04469.

110: Yugeng Liu and others, "Watermarking Diffusion Model" (*arXiv*, 21 May 2023) DOI: 10.48550/arXiv.2305.12502; Chenxi Gu and others, "Watermarking Pre-trained Language Models with Backdooring" (*arXiv*, 10 February 2023) DOI: 10.48550/arXiv.2210.07543.

Integrating Watermarks

Cloud AI providers can deploy various watermarking methods across the layers described above. In-processing transformations generally are attempted at the model layer, while post-processing approaches are typically applied at the filters and transformations stage. At the time of writing, however, the various cloud companies have taken substantially different approaches to watermarking. Google has been the most active by far, having substantially invested in its SynthID watermarking suite, which is currently enabled by default for all of its Gemini models (although it is up to clients whether they wish to watermark the output of custom models, such as open-weight models they use on Google's cloud infrastructure). SynthID's approach to watermarking text is similar to the one we show in Figure 2.7, and has been open-sourced in collaboration with Hugging Face and integrated into a number of popular machine learning libraries.[111] Making the underlying technology publicly available allows others to apply a similar scheme to Google's, but does not mean anyone can detect Google-watermarked content — the detector tool is open-sourced, but users must still choose a secret key to use with it, and Google's remains secret in order to stop its watermarks from being spoofed or scrubbed.[112]

Amazon has been less of a public champion of watermarking, but has generally adopted a similar approach to the one taken by Google. Amazon states that it watermarks outputs from its Titan image generator and provides a public detector, but it does not appear to watermark the outputs from other models, whether its own or those of a third party.[113] This sets up a tension between cloud intermediaries that do not see themselves as liable for watermarking others' models, and regulators and courts, who may disagree.

There is no credible evidence that, at the time of writing, Microsoft and OpenAI use invisible watermarking at all for text. Both use the C2PA standard for secure metadata, which is widely misreported as applying a watermark. Providing secure metadata alongside an image does not constitute a watermark by the scientific understanding of the term, as such metadata is inherently designed to be perceptible and is not in any way robust to removal. C2PA does not claim to produce watermarking standards — it refers to these within its standard as something to be used in conjunction with its secure metadata.[114]

OpenAI appears not merely to have declined to watermark text, but to have actively resisted watermarking. The issue has seemingly divided employees inside the company. It seems likely that the then-OpenAI-employed quantum computing expert Scott Aaronson was the first to

111: Sumanth Dathathri and others, "Scalable Watermarking for Identifying Large Language Model Outputs" (2024) 634(8035) Nature 818 DOI: 10.1038/s41586-024-08025-4; Sumedh Ghaisas and others, "Introducing SynthID Text" (*Hugging Face*, 17 February 2025) https://huggingface.co/blog/synthid-text accessed 7 August 2025.

112: This is in tension with the requirements in the European Commission guidance on watermarking under the AI Act, which states that the principle of interoperability means that detectors should be able to operate in a local, privacy-preserving way — which sits awkwardly with an approach that attempts to keep the private key secret and centralized. Guidelines on the Implementation of the Transparency Obligations for Certain AI Systems under Article 50 of Regulation (EU) 2024/1689 (the 'AI Act', C(2026) 5054 final) (n 102) para 76.

113: Amazon, "Watermark Detection for Amazon Titan Image Generator Now Available in Amazon Bedrock" (*Amazon Web Services, Inc*, 23 April 2024) https://aws.amazon.com/about-aws/whats-new/2024/04/watermark-detection-amazon-titan-image-generator-bedrock/ accessed 7 August 2025.

114: Coalition for Content Provenance and Authenticity, "Content Credentials: C2PA Technical Specifications (Version 2.1)" (*C2PA*, 2025) https://spec.c2pa.org/specifications/specifications/2.1/specs/C2PA_Specification.html#_soft_bindings accessed 7 August 2025, s 2.4.2.

invent a scheme resembling Figure 2.7 for text in 2022, before the launch of ChatGPT.[115] This system was worked on internally for at least two years and a fully functional version was built up for deployment;[116] however, despite the firm's enormous publication output, it appears from our research that no papers on watermarking have ever been authored by someone listing an OpenAI affiliation. Instead, the innovative deployment "sat around," with the company particularly concerned that customers would "rebel," or in the absence of sectoral cooperation, switch to a competing language model.[117] The brief life of watermarking at OpenAI came to a close following market research OpenAI commissioned in April 2023, eventually leaked to the *Wall Street Journal*, in which nearly 30% of respondents claimed that they would switch providers if OpenAI began watermarking ChatGPT outputs.[118] The firm ditched any watermarking plan soon afterward, and has since written negatively about watermarks in its response to a U.S. government consultation.[119] Instead, they have promoted a classifier tool they claim can identify AI images, although it is notable that the firm discontinued a similar text classifier tool "due to its low rate of accuracy" and never replaced it.[120] Although the company has "made a commitment to develop and deploy mechanisms that enable users to understand if audio or visual content is AI-generated," it has conspicuously made no such pledge relating to textual content.[121]

LOGGING

Logs are important for cloud providers. Conformity with international technical cybersecurity standards requires technology firms to produce, keep and analyze logs recording user activities, exceptions, faults and other relevant events.[122] Legal obligations for the logging of machine learning systems also increasingly exist. For instance, European data protection law places logging obligations on data processing systems used for law enforcement purposes.[123] The EU AI Act further requires that either the provider or deployer of AI systems for certain high-risk applications should log how the system is used.[124] It also notes that generative

115: Aaronson, "My AI Safety Lecture for UT Effective Altruism" (n 105); Scott Aaronson, "Watermarking of Large Language Models" (*Talk given at the Large Language Models and Transformers workshop, Simons Institute for the Theory of Computing*, 17 August 2023) https://simons.berkeley.edu/talks/scott-aaronson-ut-austin-openai-2023-08-17 accessed 7 August 2025.

116: Deepa Seetharaman and Matt Barnum, "There's a Tool to Catch Students Cheating With ChatGPT. OpenAI Hasn't Released It." (*Wall Street Journal*, 4 August 2024) https://www.wsj.com/tech/ai/openai-tool-chatgpt-cheating-writing-135b755a accessed 7 August 2025; Aaronson, "Watermarking of Large Language Models" (n 115) (revealing a test implementation was coded by Hendrik Kirchner).

117: Aaronson, "Watermarking of Large Language Models" (n 115) at 1:00:40.

118: Seetharaman and Barnum (n 116).

119: OpenAI, "Response to NIST Executive Order on AI" (2 February 2024) https://openai.com/global-affairs/response-to-nist-executive-order-on-ai/ accessed 7 August 2025.

120: OpenAI, "New AI Classifier for Indicating AI-written Text" (31 January 2024) https://openai.com/index/new-ai-classifier-for-indicating-ai-written-text/ accessed 7 August 2025.

121: ibid.

122: British Standards Institution, *Information Security, Cybersecurity and Privacy Protection — Information Security Controls (BS EN ISO/IEC 27002:2022)* (BSI 2022) s 8.15.

123: Directive (EU) 2016/680 of the European Parliament and of the Council of 27 April 2016 on the protection of natural persons with regard to the processing of personal data by competent authorities for the purposes of the prevention, investigation, detection or prosecution of criminal offences or the execution of criminal penalties, and on the free movement of such data, and repealing Council Framework Decision 2008/977/JHA [2016] OJ L119/89 (Law Enforcement Directive) art 25.

124: AIA, art 12.

AI systems may use logging as part of their pipeline for marking content as AI-generated.[125] Content moderation decisions and the reasons for them must also be logged in Europe and passed to the European Commission.[126]

Logging can allow generated content to be compared against logged content to see which provider, and potentially which user, it came from. Various researchers from cloud companies including Google and OpenAI have publicly considered this idea,[127] although Google has since explicitly distanced itself from its prior research on the topic for privacy reasons.[128]

It is not entirely clear what kinds of logs cloud AI providers collect, or for how long and under what conditions they retain them. Such providers do however report using such logs in investigations. OpenAI and Microsoft have written about the various organized criminal operations they claim to have disrupted, including, variously, Russian, Chinese and Iranian state intelligence using LLMs to debug malware, generate propaganda content and conduct offensive research with known cybersecurity threat actors.[129] Some of these efforts appear to have been detected following a tip-off, and others following internal exploration or anomaly detection algorithms.[130] The next step after awareness? Read the logs.

Keeping logs makes them a target for government data requests. These requests typically target either 'communications' data — metadata such as the parties to a communication and their location — or 'content' data, meaning the messages themselves.[131] Legal requirements are typically steeper for accessing content than for accessing communications data. Major companies report some data relating to the requests they receive, but it can be confusing to interpret, as some regimes prohibit publication or mandate a reporting delay. Furthermore, cloud providers have not yet separated out requests relating to their AI systems from general cloud requests. OpenAI's reporting is therefore instructive as to AI-specific trends. As shown in Figure 2.8, between 2023 and 2025, requests for both content data and non-content metadata, disclosures on the basis of such requests and the accounts implicated in those disclosures have rapidly increased. Most requests, especially content-related ones, are granted.

In any case, this data from OpenAI also excludes certain other information, such as data disclosed to the NSA under the Foreign Intelligence Surveillance Act (FISA). FISA data can only be reported with a delay, which varies with the granularity of data the firm wishes to report, but firms that have never before received an order of this severity are gagged from any reporting at all for at least 18 months.[132] Certain orders can also come in advance of a data request. Proactive data retention obligations can be placed on technology providers, applying

125: AIA, recital 133.

126: Regulation (EU) 2022/2065 of the European Parliament and of the Council of 19 October 2022 on a Single Market For Digital Services and amending Directive 2000/31/EC [2022] OJ L265/1 (DSA) art 24(5).

127: Kalpesh Krishna and others, "Paraphrasing Evades Detectors of AI-generated Text, but Retrieval Is an Effective Defense" (2023) 36 Advances in Neural Information Processing Systems 27469 https://dl.acm.org/doi/10.5555/3666122.3667317 accessed 7 August 2025; Aaronson, "Watermarking of Large Language Models" (n 115).

128: Dathathri and others (n 111) 818.

129: Microsoft, "Staying Ahead of Threat Actors in the Age of AI" (*Microsoft Security Blog*, 14 February 2024) https://www.microsoft.com/en-us/security/blog/2024/02/14/staying-ahead-of-threat-actors-in-the-age-of-ai/ accessed 9 August 2025.

130: OpenAI, "Influence and Cyber Operations: An Update" (*OpenAI*, October 2024) https://cdn.openai.com/threat-intelligence-reports/influence-and-cyber-operations-an-update_October-2024.pdf accessed 7 August 2025.

131: See generally Bernard Keenan, *Interception: State Surveillance from Postal Systems to Global Networks* (MIT Press 2025) DOI: 10.7551/mitpress/15654.001.0001.

132: 50 U.S.C. §1874 (2023). U.S. CLOUD Act data may also be excluded, such as data requested by the UK or Australia without using the MLAT process.



Figure 2.8: Government requests for OpenAI user data, 2023–2025. Data collated from OpenAI, "Trust and Transparency" (*OpenAI*, 2025) https://openai.com/trust-and-transparency/ accessed 8 August 2025, graph by authors.

to all records, as can reactive data preservation requests, which relate to specific circumstances or investigations. Fundamental rights battles have raged in European courts concerning the extent to which horizontal data retention obligations clash with core protections of the rights to private life and freedom of expression.[133]

CLOUDSPOTTING

There are multiple potential approaches that cloud AI providers can take to prevent the illegal misuse of their systems. There are also various approaches that they can take to try to better investigate that misuse after it has happened. However, the cloud environment is complex and has varying features and affordances: there is not just one way to train, deploy or query a model through a cloud provider. These infrastructural choices affect when and how the described safety 'layers' can work, and whether they can meaningfully provide either brakes on unwanted activity or loops to be hooked onto for further investigation.

An important distinction can be made between what are often referred to as *pooled*, *managed* or *unmanaged* compute in the cloud. Understanding these distinctions helps us understand when safety features can be applied at all, and with what efficacy and robustness.

133: See generally Eleni Kosta and Irene Kamara (eds), *Data Retention in Europe and beyond: Law and Policy in the Aftermath of an Invalidated Directive* (Oxford University Press 2025).

POOLED COMPUTE

AI companies tend to combine their computing power to sell homogeneous and opaque services to their users. This business model, typically called 'AI-as-a-service' or 'serverless,' allows users to interact with pre-set models and be charged per query (or by characteristics of a query, such as its length).

Users interact with these models through either Web interfaces, like ChatGPT, or application programming interfaces (APIs). Web interfaces will be familiar to readers. APIs — structured methods to ask a computer to do something — are common to all aspects of cloud computing, but are especially essential for pooled computing. A call to a large language model API from a UNIX command line interface typically follows the structure below, initially created by OpenAI and mimetically adopted by the rest of the industry.

```
curl https://api.openai.com/v1/responses \
  -H "Content-Type: application/json" \
  -H "Authorization: Bearer $API_KEY" \
  -d '{
    "model": "gpt-4.1",
    "input": "Who is the fairest of them all?"
  }'
```

Following this query, a computer will receive a JSON object — a predictable text response structured with curly brackets, quotes and commas. If everything went well, it will contain metadata related to the processing as well as the response to the input. Developers can build software to extract what they need from this.

Pooled computing accessed through APIs is efficient for cloud firms because they can provide the same service to many entities with minimal time-intensive support. Each query can be transformed and directed behind the scenes for cost-effectiveness. It can be sent to whichever data center has current spare capacity; batched with other queries to ask a model multiple things at the same time to soak up all available compute; or, if detected as a less complex query, punted to a less expensive model. Some APIs support limited and structured forms of customization. Providers are very quiet about how they actually do this, but it is unlikely to allow users to fine-tune an entire model, as this would create an enormous hosting cost for the provider, who would have to store a duplicate of the existing model. Instead, as Microsoft notes, a technology called low-rank adaptation (LoRA) is typically used, which is effectively a more limited, partial and compressed form of fine-tuning that can be saved as a plug-in for future use.[134] Technologies that alter the prompts to customize model behavior are also sold this way, including retrieval-augmented generation (RAG), where models are given instructions on how to query customers' databases or the Web. LoRAs and RAGs are discussed extensively in Chapters 3 and 4 respectively.

Out of all the infrastructural choices to provide compute for AI in the cloud, pooled approaches can be the most secure against malicious misuse. Assuming that all the services behind the API are delivered by a single cloud provider, that provider can quite easily design

134: Microsoft, "Customize a Model with Azure OpenAI in Azure AI Foundry Models" (*Azure OpenAI*, 2 July 2025) https://learn.microsoft.com/en-us/azure/ai-foundry/openai/how-to/fine-tuning accessed 9 August 2025.

visibility and manipulability into everything, from the beginning of an interaction when an API is called to the endpoint when the result is delivered. The provider can choose the model and the prompt, add filters and transformations, monitor usage and introduce human review as desired. Users, on the other hand, can be given little information — just the output given the input, with the rest shrouded in mystery. Users might try to avoid behavioral detection over time with different accounts or API keys, but such behavior can be made costly by the provider.

MANAGED COMPUTE

Managed compute gives greater customization than pooled compute, while attempting to abstract away difficult tasks that come with running AI systems from scratch, such as managing the hardware, the software and the networks between them. This area is commercially known as "MLOps" or "platform-as-a-service," and is offered by all major cloud players. It typically resembles a sprawling set of modular services with a common umbrella brand such as Amazon SageMaker, Azure Machine Learning or Google Cloud Vertex AI.[135]

Users of managed compute services are given tools to store and ingest data, a choice of an array of existing models and tools to fine-tune them and connect them to other systems and processes. Both proprietary and open-weight models are available, although proprietary models provided by the cloud provider are less customizable than open-weight models — lest a user steal the structure and weights — so in practice often resemble the pooled computing option above.[136]

Managed compute is a more complex business proposition than pooled compute. Cloud providers can still reap substantial efficiency benefits from pooling the same infrastructure across many customers, but have to make sure these tricks do not break what users are trying to do. It's also a more complex safety proposition. The layered approach we described above is harder to apply in its entirety in this infrastructural set-up due to the greater configurability of the systems that are available.

Generally, it is harder for a cloud provider to build in meaningful controls at the model layer, given the greater ability to fine-tune models, which might break such controls, as well as the typical availability of third-party, open-weight models. Because users can pick and choose which models to use, including community models uploaded by anyone to model marketplaces like Hugging Face, there are limited assurances against intentional misuse. Such assurances are further limited by open-weight models that are highly competitive with closed models, such as Alibaba's Qwen.

Applying filters and transformations intended as brakes against misuse is not impossible, given that the cloud provider can wrap them around the general building blocks made available to users. Yet such filters cannot be tested beforehand in all permutations of configurability

135: Fernando van der Vlist, Anne Helmond, and Fabian Ferrari, "Big AI: Cloud Infrastructure Dependence and the Industrialisation of Artificial Intelligence" (2024) 11(1) Big Data & Society 20539517241232630 DOI: 10.1177/20539517241232630 accessed 4 April 2024.

136: See e.g. Amazon, "Use Proprietary Foundation Models from Amazon SageMaker JumpStart in Amazon SageMaker Studio" (*AWS*, 27 June 2023) https://aws.amazon.com/blogs/machine-learning/use-proprietary-foundation-models-from-amazon-sagemaker-jumpstart-in-amazon-sagemaker-studio/ accessed 2 August 2025.

or fine-tuned components, and thus risk failing unpredictably. At the time of writing, cloud providers are only wrapping certain proprietary models in filters, such as Google's Gemini models and Microsoft's resold OpenAI models, and providing them much as pooled compute is provided. This likely stems from the reputational risk concerns that these providers have with their flagship brands, which in turn might lead to contractual requirements when these models are resold to third parties. For other models, including similarly powerful open-weight ones, filters are an optional — typically paid-for — component, just like any other managed computing building block. Tools are available to support the explicit shift of these kinds of filtering responsibilities to customers. For example, Microsoft provides a safety leaderboard where customers can see the safety qualities of the model layer alone, filter-free, to make a decision on what kind of safety, if any, to apply.[137]

For the cloud services themselves, the many potential configurations of managed compute make detailed usage monitoring difficult, although not impossible. Current documentation made available by the large firms is not explicit as to whether otherwise unfiltered managed compute components come with the basic, compulsory scanning of pooled computing environments, such as for child sexual abuse material. In general, the approach to trust and safety within this type of compute is nascent, patchy and still in the process of consolidating.

UNMANAGED COMPUTE

Finally, there are 'unmanaged' forms of cloud provision. This set-up is often referred to as 'infrastructure-as-a-service.' It is the closest thing that the industry has to a rental model, where all the computing components, rather than a more abstract service, have prices, and remote control is handed over to the customer. These machines can be *virtual*, abstracted so the user *appears* to be renting a specific set of hardware, which on the back-end is really pooled and shared, or can be *real*, with particular physical resources, such as a GPU, assigned exclusively to an individual or organization.

Giving the user control of the most rudimentary parts of the infrastructure means they can choose what software runs on it, from the operating system up. Providers often try to help with some pre-prepared *images* — snapshots of an operating system at an early stage of set-up, preinstalled with useful software or security tools — but customers can also bring their own, and indeed, in the European Union, have a legal right to be able to.[138]

This type of unmanaged set-up is the most difficult to safeguard. Proprietary models offered by firms like Amazon or Google are typically unavailable through unmanaged compute deployments, as, given the user's root control over devices, it would be trivial for savvy users to exfiltrate and steal the models' structure and parameters and thus the cloud provider's intellectual property.

137: Microsoft, "Explore Model Leaderboards in Azure AI Foundry Portal" (*Azure AI Foundry*, 25 June 2025) https://perma.cc/4699-YU6Y accessed 3 August 2025.

138: This is under the law on cloud switching, where providers need to permit users to port their data, which would include their operating systems and similar, from one service to another, see Regulation (EU) 2023/2854 of the European Parliament and of the Council of 13 December 2023 on harmonised rules on fair access to and use of data and amending Regulation (EU) 2017/2394 and Directive (EU) 2020/1828 [2023] OJ L (Data Act) art 23 (there is ability to restrict this functionality for cybersecurity reasons, but it must not delay switching).

Fully unmanaged compute is also the most difficult for providers to monitor. While providers can have access to a form of visibility known as *virtual machine introspection* — the view that the cloud provider has from their *hypervisor* software, or the system they use to orchestrate and provision all their virtual machines — typically this can only provide high-level information in real time. Hypervisors have to keep some distance from virtual machines in order to avoid being a vector for attacks or other instances where virtual machines leak information to one another.[139] Providers can also look into what is happening in their systems by scanning snapshots they take of memory. Some providers offer paid-for security services where they make copies of the memory of virtual machines and probe them for threats. Google, for example, requires a subscription to such a service in order for firms to benefit from its aforementioned cryptojacking indemnification.[140]

Unfortunately, this approach is not particularly practical for the problem of AI misuse. First, memory scans are expensive and cumbersome to store and thus only taken periodically. (Google does them once a day in its efforts to detect cryptomining, and seeks to sniff out impermissible infrastructure or programs through various statistical techniques.) Since AI is dual-use and ambivalent, and typically permitted on unmanaged compute, in contrast to cryptomining, the core policy question relates to *how* it is being used. Scanning is in and of itself not helpful, as content can be set up to be deleted immediately after it is generated and transmitted, evading periodic system scans.

Cloud providers can also get visibility into virtual machines through another method that transcends mere scanning: "agent-based monitoring." This involves asking their customers to install pieces of software called *guest agents* on their devices.[141] These are not 'AI agents' as often discussed, but instead refer to bespoke reporting and management tools that pass information to the cloud provider on aspects of machine usage only visible from within. They are typically extremely trusted by the virtual machine and given high privileges, enabling them to access all manner of files and run all manner of scripts.

Guest agents have near-limitless potential visibility into what a user is doing with a computer, but they can also be fooled and subverted. The trust and privilege placed in this software can also lead to systemic risk when it fails or is compromised, as the world discovered with the 2024 global failure of CrowdStrike's similarly privileged endpoint security tool. Its shutdown led to a deluge of looping "blue screens of death" on computers around the world, disrupting many hospitals and, as the authors of this book discovered while traveling to get together for a weekend of writing, airports.[142]

To our knowledge, agent-based monitoring has never been publicly used for something as

139: Tal Garfinkel and Mendel Rosenblum, "A Virtual Machine Introspection Based Architecture for Intrusion Detection" in *Proceedings of the Internet Society's 2003 Symposium on Network and Distributed System Security* (NDSS, 2003).

140: Google, "Virtual Machine Threat Detection Overview" (*Google Cloud Security Command Center*, 1 August 2025) https://cloud.google.com/security-command-center/docs/concepts-vm-threat-detection-overview accessed 3 August 2025; Google, "Cryptomining Detection Best Practices" (n 29).

141: Examples include AWS Systems Manager; Google Guest Environment; or Azure VM Agent.

142: Lily Hay Newman, "How One Bad CrowdStrike Update Crashed the World's Computers" (*Wired*, 19 July 2024) https://www.wired.com/story/crowdstrike-outage-update-windows/ accessed 3 August 2025; Jeffrey L Tully and others, "Patient Care Technology Disruptions Associated With the CrowdStrike Outage" (2025) 8(7) JAMA Network Open e2530226 DOI: 10.1001/jamanetworkopen.2025.30226; Chris Stokel-Walker, "CrowdStrike Tech Outage Shows the Precarious Nature of Our Digital World" (*The i Paper*, 19 July 2024) https://inews.co.uk/news/technology/crowdstrike-global-outage-fragile-world-it-system-3179380 accessed 3 August 2025.

complex as AI misuse detection. That would involve monitoring to see if a user is using a machine learning tool and then robustly attempting to intercept some set of its inputs and/or outputs. It is not necessarily impossible in theory, but it would be an extremely invasive technology, with more in common with spyware than ordinary trust and safety tooling. The deployment of such software would come with many risks, not just by potentially introducing further cybersecurity vulnerabilities, but also by providing an ideal scanning and monitoring vector to be covertly weaponized by intelligence agencies using secret warrants.

This kind of system would likely also be fragile and break in unexpected ways. Conceptually, it is not difficult to imagine attackers finding ways to query models through methods that would not be registered as such, or to hide their real queries using transformations or other methods, such as piping in raw, difficult-to-scan mathematical instructions from an external, unmonitored computer. To be effective, it would also necessitate that cloud providers *require* the agent to be installed, likely checking this and disabling non-compliant machines or restricting their GPU access.

CLOUDS AHEAD

How can various actors work in the cloud layer to try to detect and disrupt undesirable generative AI activity? This chapter has sketched out the contours of this landscape. APIs and — if sufficiently restrained — managed compute can be subject to a layered approach to trust and safety. Though promising, the layered approach already has its limitations. It becomes even more limited as we move away from structured compute to fully unmanaged compute, with much reduced possibility for insight and intervention.

Limiting the possibility of misuse by determined actors in situations of less managed compute requires interventions that could be characterized as extreme and invasive. Monitoring and surveillance of customer cloud setups would have to increase. Cloud hyperscalers may have to abstract away a lot of customizability, as customizability can allow the layers of filters, transformations, model predispositions and prompt steering to be circumvented. Instead, they would be transforming unmanaged compute into managed compute, providing computational building blocks that have safety and limitations built in, rather than access to the 'raw metal' of the underlying computers themselves. These changes would be akin to forcing AI developers to move from Lego to Duplo. There are some things that you just can't build with Duplo.

In its most intensive form, providers could try to limit the models available within managed compute only to certain, tested, perhaps proprietary models, not fine-tuned far from their initial setups, and to detect and block users deploying anything else. This would be quite an astounding prohibition on open computing, and, if it were a legal obligation, would likely be challenged under regimes such as the United States' First Amendment or the European Union's freedom to conduct a business.[143] Yet it is not unthinkable. Again, motivated by geopolitics rather than criminal activity, the United States has been deliberating, even agonizing, over whether and how to limit business access to or use of Chinese AI models.[144] While

143: Charter of Fundamental Rights of the European Union [2012] OJ C326/391 (Charter) art 16.

144: David McCabe and others, "White House Whipsaws Silicon Valley (and Itself) Over A.I. Rules" (*The New York Times*,

businesses can be intimidated by courts, regulators and fines, meaningfully limiting access for determined criminal enterprises, many of whom will be outside the jurisdiction, is a different matter.

Overall, in its most open form, cloud compute of the unmanaged kind is extremely easy to misuse without detection. The few policy options that might help mitigate this are limited and fairly unsatisfactory.

The first policy option would be to limit access to unmanaged compute, at least with GPUs and hardware suitable for AI deployment, to attempt to exclude actors without the technical and organizational safeguards to ensure that these resources are not abused. This would entail, effectively, a licensing model for trusted entities, and a segmentation of the problem into the governance of licensed, trusted entities that have open-ended compute, and the monitoring of only pooled or heavily managed compute for everyone else. This might require monitoring obligations to be placed on cloud providers. Although this kind of policy might seem reasonable right now, note that stronger and stronger GPUs are increasingly embedded in consumer devices, and such GPUs are likely to play an important role in day-to-day computing. Restrictions may have few societal consequences when GPU use on unmanaged compute is only sought for esoteric reasons by a few R&D-centric organizations, but if such hardware becomes integrated into general-purpose computing and the lines are blurred even more than they are today, this kind of requirement will have a greater social and economic impact.

Forms of these requirements have already begun to emerge, fueled not by crime but by geopolitics. In January 2024, the U.S. Commerce Department began a consultation period for a new set of rules that would require cloud computing entities to verify the identity of foreign customers when selling services to train AI models with certain malicious capabilities.[145] More recently, at the time of writing, a proposed law called the Remote Access Security Act (RASA) passed the U.S. House. This law effectively alters the concept of 'export' to mean that selling access abroad to domestic cloud compute can clearly fall under U.S. controls designed to impose geopolitical power. Notably, this law might provide a firmer basis for the legally tenuous actions of the U.S. Commerce Department to suspend access to Anthropic's Fable model in June 2026 for foreign nationals, a case in which it was debated whether provision of this model over the Internet could count as an 'export.'[146] While these rules do not squarely take aim at the specific types of malicious use we focus on here — instead responding to current AI geopolitics — they all indicate that policymakers are becoming more willing to restrict compute in new, more granular ways.

The second policy option would be 'safety by design': to reduce the generativity of unman-

4 August 2026) https://www.nytimes.com/2026/08/04/technology/ai-washington-regulation-whiplash.html accessed 5 August 2026.

145: President of the United States of America, "Executive Order 14110 of October 30, 2023: Safe, Secure, and Trustworthy Development and Use of Artificial Intelligence" (2023) 88(210) Federal Register 75191 https://www.federalregister.gov/documents/2023/11/01/2023-24283/safe-secure-and-trustworthy-development-and-use-of-artificial-intelligence accessed 20 June 2024; Department of Commerce, "Taking Additional Steps To Address the National Emergency With Respect to Significant Malicious Cyber-Enabled Activities" (2024) 89(19) Federal Register 5698 https://www.federalregister.gov/documents/2024/01/29/2024-01580/taking-additional-steps-to-address-the-national-emergency-with-respect-to-significant-malicious accessed 20 June 2024.

146: Alex Zhao, "Is Access to Fable an Export?" (*Harvard Law Review Blog*, 26 June 2026) https://harvardlawreview.org/blog/2026/06/is-access-to-fable-an-export/ accessed 5 August 2026; Alan Rozenshtein, "A Kill Switch for Frontier AI" (*Lawfare*, 15 June 2026) https://www.lawfaremedia.org/article/a-kill-switch-for-frontier-ai accessed 5 August 2026.

aged compute as a whole by effectively abolishing unmonitored (or unmonitorable) compute as a service. This effectively would be to concede that the risks from AI misuse are so great that the whole sector of unmanaged compute would need to be folded into managed compute, limiting the way tasks can be structured and executed in order to allow external monitoring and intervention.

These options would need to be applied to cloud services globally to be effective against internationally mobile criminal groups. Voluntary compliance, while possible, is unlikely. Any attempt to prohibit unmanaged computing would likely instantly result in a competitor jumping eagerly into that gap unless there was a multi-jurisdictional effort to prevent this from happening. It would be heavily invasive and controversial, and may fail in some jurisdictions on constitutional grounds. Its effectiveness would also depend on the concentration of the cloud market — if as highly concentrated as it is at the time of writing, the actions of a few providers may make a real difference, but on the flipside, this leaves only a handful of firms gatekeeping the means of computation in society.

Controlling the cloud layer is not the only game in town, however. After all, many models are downloadable and can be deployed without the cloud, on a user's personal device. This may increase further in the future with more efficient and powerful devices, particularly as the kind of harms we have been discussing do not always require the most powerful models to perpetrate. It is to this — the challenges of *local* governance — that we now turn.